

SCP PART#: 14/4-GY

Description : 4C/14 AWG 19-Strand BC, Unshielded MultiPurpose, UL CMR PVC - Gray
 1000 FT Spool

02/22

General Specification of Product :

Final Diameter : 0.267 inches 6.782 mm

Total Cable Weight: 108.0 kg/km 72.6 lbs/1000 ft

Conductor : 4 Cond -14 AWG 19 Strand SBC Cond.

Insulation : PVC

Outer Jacket : PVC

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 14/4 - - - (UL) CL3R E198137-SCP
 (UL) C(UL) CMR UNSH 4/C 14 AWG STR BC AUDIO ONLY - - -
 ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C: 2.7 Ohms / 1000 ft

Mutual Capacitance : 22.3 pF/ft

Impedance : 75 Ohms

Velocity of Prop : 70 %

Inductance. : 1.2 mH/km

Additional Information :

Cabled OD Avg: 0.237

Ins Thickness: 0.010

Jkt Thickness: 0.015

Certified: UL CL3R / UL C(UL) CMR

Flame Rating: Riser

Max Voltage: 300V

Packaging: Plywood Spool 12 x 12 x 5"

Packaged Weight: 74 lbs / 32 kgs

(All of the above values are approximated to within +/- 10%)