



# Structured Cable Products™

Quality Installations Deserve Quality Products

www.scp5e.com  
 sales@scp5e.com  
 Direct: 954-327-5770  
 Toll Free: 866-470-5742

**SCP PART#: 14/4SH-GY**

UPC: 810070010270

**DESCRIPTION:**

Shielded Riser 4/C 14/19 AWG SBC PVC Insulation, Gray PVC Riser Jacket, 1000 FEET/305M

**General Specification of Product :**

<b>Final Diameter :</b>	0.267 inches	6.782 mm
<b>Total Cable Weight:</b>	104 kg/km	70 lbs/1000 ft
<b>Conductor :</b>	14 AWG 19 Strand SBC Cond.	
<b>Insulation :</b>	PVC	
<b>Shield :</b>	Foil Shield 1.0	
<b>Drain \ Ground:</b>	24 AWG 7 Strand STC Cond.	
<b>Outer Jacket :</b>	PVC	

**Print Notes :** Sequentially marked per 2FT (0 - infinity)

**Standard Print :** STRUCTURED CABLE PRODUCTS - - - P/N 14/4SH - - - (UL) CL3R  
 E198137-SCP (UL) C(UL) CMR SHIELDED 4/C 14 AWG AUDIO ONLY - - -  
 ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

**Electrical Characteristics :**

DC Resistance 25°C:	2.6 Ohms / 1000 ft
Mutual Capacitance :	73.7 pF/ft
Cond to Shield Cap. :	133.0 pF/ft
Impedance :	40 Ohms
Velocity of Prop :	63 %
Inductance. :	1.3 mH/km

**Additional Information :**

Cabled OD Avg: 0.241  
 Ins Thickness: 0.011  
 Jkt Thickness: 0.017  
 Certified: UL CL3R / UL C(UL) CMR  
 Flame Rating: Riser  
 Max Voltage: 300V  
 Packaging: Plywood Spool 12 x 12 x 5"  
 Packaging Weight: 70 lbs / 32 kgs

( All of the above values are approximated to within +/- 10% )

**QMS Registered ISO 9001**

3091404.10S.1000