

<b>SCP PART#: 16/4-GY</b>
---------------------------

DESCRIPTION : 4C/16AWG BC 26 STRAND, Unshielded Multipurpose,UL CMR,PVC  
 JKT-Gray-1000FT BOX

**Construction Characteristics:**

Conductor	Material	Bare Copper
	Size	16AWG X 4C
	Construction	26/0.25+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.24mm
	AVG.Thickness	0.26mm
	Diameter	2.0+/-0.05mm
	Colors	Black & Red & White & Green
Jacket	Material	PVC
	Min.Thickness	0.45mm
	AVG.Thickness	0.50mm
	Diameter	6.0+/-0.20mm
	Rip Cord	Nylon
	Color	Gray
Bend radius	Min 15D/77mm	

**Electrical & Physical Characteristics:**

Operating Temperature Range	- 20°C + 75°C
Minimum installation temperature	0°C + 40°C
Conductor Resistance(16AWG)	Max 15.5ohm/km at 20°C
Dielectric Strength	Min AC1.5KV
Insulation Resistance	Min 50MΩ*km at 20°C
Rated Voltage	Max 300Volts

**Marking:**

STRUCTURED CABLE PRODUCTS --- 16/4 --- UNSH 4C 16 AWG STRANDED---  
 E198137 SCP3 (UL)C(UL) CMR ---PVC JKT EN50575:2014 CE Dca EU RoHS EC  
 ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 XXXFEET

**Packaging:**

Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
24.0kgs	405X258X418	1000ft/Box	30/20