


SCP PART#: 18/2DB-500

2C/18 AWG 16 STRAND OXYGEN FREE COPPER SPEAKER CABLE, WATER PROOF,LLDPE JKT

Rev03/21



Standard:

EU RoHS 2011/65/EU Compliant

Construction Characteristics:

Conductor	Material	Stranded Bare Copper
	Size	18AWG X 2C
	Construction	16/0.254+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.24mm
	AVG.Thickness	0.26mm
	Diameter	1.70+/-0.05mm
	Colors	Black & Red
Screen	Core wrap	PE Tape
	Filler	Water proof
Jacket	Material	LLDPE
	Min.Thickness	0.70mm
	AVG.Thickness	0.80mm
	Diameter	5.2+/-0.20mm
	Rip Cord	Nylon
	Color	Black
Bend radius	Min 15D/80mm	

Electrical & Physical Characteristics:

Operating Temperature Range	- 20°C + 75°C
Minimum installation temperature	0°C + 40°C
Conductor Resistance(18AWG)	Max 22.8ohm/km at 20°C
Insulation Resistance	Min 50MΩ*km at 20°C
Dielectric Strength	Min AC1.5KV
Rated Voltage	Max 80Volts

Marking:

STRUCTURED CABLE PRODUCTS -- 18/2DB -- 2C 18AWG 16 STRAND OFC DIRECT BURIAL WATER BLOCK TAPE - LLDPE JKT - EU RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***FEET

Packaging:

Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
5.8kgs/12.786lbs	270X160X160	500ft/Spool	96