

SPECIFICATION SHEET

www.scpcat5e.com
sales@scpcat5e.com

14-May-2014

Product Number : 18/2FPLR-SH

RoHS

Description : 2C/18 AWG SOLID FPLR SHIELDED PVC- RED- 1000 FT SPOOL

Conductor : 10 AWG Solid HBC Cond.	
Total Cable Weight : 31 kg/km	Final Diameter : 0.153 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 4 Ohms / 1000 ft	Mutual Capacitance : 61.6 pF/ft
Impedance : 61.4 Ohms	Cond to Shield Cap : 115.4 pF/ft
Velocity of Prop : 62 %	Inductance. : 4 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 18/2FPLR-SH - RISER FIRE ALARM CABLE (UL) CL2R/CL3R E198137 OR FPLR (UL) C(UL) CMG CMR SHIELDED 2/C 18 AWG SOLID PVC JKT --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.111	NEC Articles: 800, 760, 725
Ins Thickness: 0.010	Shield: AL FOIL
Jkt Thickness: 0.015	Min. Bend Radius/Minor Axis: 1.057 inches
Certified: UL CL2R/CL3R OR FPLR/CMG/CMR	Operating Temperature : -20°C to 60°C
Flame Rating: Riser	Standard UL Temp : 60°C
Max Voltage: 300V	

Package Weight: 16 lbs / 7.27 kgs

(All of the above values are approximated to within +/- 10%)