Structured Cable Products
Quality Installations Deserve Quality Products

SPECIFICATION SHEET

Phone: 866-470-5742
sales@scpcat5e.com
www.scpcat5e.com

30-May-2014

Product Number : **18/6SHP**

RoHS

Shielded Cable 6/C 18/7 AWG SBC
PVC PLENUM Insulation
White PVC PLENUM FT6 Jacket
1000 FEET Plywood Spool

Conductor : 18 AWG 7 Strand SBC Cond.	
Total Cable Weight : 73 kg/km	Final Diameter : 0.216 inches
Insulation : PVC	Jacket : PVC
Shield : Foil Shield 0.75	
Drain : 24 AWG 7 Strand STC Cond.	
DC Resistance 25°C: 6 Ohms / 1000 ft	

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 18/6SHP --- (UL) CL2P/CL3P E132885 OR FPLP 75°C (UL) C(UL) CMP FT- 6 SHIELDED 6/C 18 AWG --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Missing Electrical Data
Cabled OD Avg: 0.205
Ins Thickness: 0.008
Jkt Thickness: 0.015
Certified: UL CL2P/CL3P OR FPLP/CMP
Flame Rating: Plenum
Max Voltage: 300V

(All of the above values are approximated to within +/- 10%)

7601806BPV6.02S.1000