



Structured Cable Products

Quality Installations Deserve Quality Products

SPECIFICATION SHEET

Phone: 866-470-5742

sales@scpcat5e.com

www.scpcat5e.com

30-May-2014

Product Number : **18/8SHP**

RoHS

**Shielded Cable 8/C 18/7 AWG SBC
PVC PLENUM Insulation
White PVC PLENUM FT6 Jacket
1000 FEET Plywood Spool**

Conductor :	18 AWG 7 Strand SBC Cond.		
Total Cable Weight :	94 kg/km	Final Diameter :	0.240 inches
Insulation :	PVC	Jacket :	PVC
Shield :	Foil Shield 1.0		
Drain :	24 AWG 7 Strand STC Cond.		
DC Resistance 25°C:	6 Ohms / 1000 ft		

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 18/8SHP --- (UL) CL2P/CL3P
E132885 OR FPLP 75°C (UL) C(UL) CMP FT- 6 SHIELDED 8/C 18 AWG ---
ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Missing Electrical Data

Cabled OD Avg: 0.240

Ins Thickness: 0.008

Jkt Thickness: 0.015

Certified: UL CL2P/CL3P OR FPLP/CMP

Flame Rating: Plenum

Max Voltage: 300V

(All of the above values are approximated to within +/- 10%)

7601808BPV6.02S.1000