

| |
|-----------------------------|
| SCP PART#: 22/10-500 |
|-----------------------------|

DESCRIPTION: 10C/22AWG STRANDED BC,MULTIPURPOSE/SECURITY/Alarm Cable,
 UL CMR PVC JKT-White-500FT Spool

Standard: EN50575: 2014 REACTION TO FIRE CLASS Eca
 EU RoHS 2011/65/EU Compliant

Construction Characteristics:

| | | |
|-------------|---------------|---------------------------------------------------------------------|
| Conductor | Material | Stranded Bare Copper |
| | Size | 22AWG X 10C |
| | Construction | 7/0.25+/-0.004mm |
| Insulation | Material | PVC |
| | Min.Thickness | 0.20mm |
| | AVG.Thickness | 0.25mm |
| | Diameter | 1.1+/-0.05mm |
| | Colors | Black, Red, White, Green, Brown, Blue, Orange, Yellow, Purple, Gray |
| Jacket | Material | PVC |
| | Min.Thickness | 0.3mm |
| | AVG.Thickness | 0.40mm |
| | Diameter | 5.0+/-0.20mm |
| | Rip Cord | Nylon |
| | Color | White |
| Bend radius | Min 15D/65mm | |

Electrical & Physical Characteristics:

| | | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-------------|---------------------|
| Operating Temperature Range | - 20°C + 75°C | | |
| Conductor Resistance(22AWG) | Max 57.5ohm/km at 20°C | | |
| Dielectric Strength | Min AC1.5KV | | |
| Rated Voltage | Max 80Volts | | |
| Marking: | | | |
| STRUCTURED CABLE PRODUCTS --- 22/10 --- SECURITY CABLE UNSH 10C/22AWG BC STR ----- E198137 SCP3 (UL) C(UL) CL3R CMR----- PVC JKT RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***M DDMMYY | | | |
| Packaging: | | | |
| Approx.Weight | Approx.Dimension(mm) | Package | Packages per pallet |
| 9.2 kgs | 270*200*160 | 500ft/spool | 36 |