

SCP PART#: 22/12-500

 DESCRIPTION: 12C/22AWG STRANDED BC,MULTIPURPOSE/SECURITY/Alarm Cable,
 UL CMR PVC JKT-White-500FT BOX

Standard: EN50575: 2014 REACTION TO FIRE CLASS Eca
 EU RoHS 2011/65/EU Compliant

Construction Characteristics:

Conductor	Material	Stranded Bare Copper
	Size	22AWG X 12C
	Construction	7/0.25+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.20mm
	AVG.Thickness	0.25mm
	Diameter	1.1+/-0.05mm
	Colors	Black, Red, White, Green, Brown, Blue, Orange, Yellow, Purple, Gray, Pink, Teal
Jacket	Material	PVC
	Min.Thickness	0.3mm
	AVG.Thickness	0.40mm
	Diameter	5.2+/-0.20mm
	Rip Cord	Nylon
	Color	White
Bend radius	Min 15D/65mm	

Electrical & Physical Characteristics:

Operating Temperature Range	- 20°C + 75°C		
Conductor Resistance(22AWG)	Max 57.5ohm/km at 20°C		
Dielectric Strength	Min AC1.5KV		
Rated Voltage	Max 80Volts		
Marking:			
STRUCTURED CABLE PRODUCTS --- 22/12 --- SECURITY CABLE UNSH 12C/22AWG BC STR ----- E198137 SCP3 (UL) C(UL) CL3R CMR----- PVC JKT RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***M DDMMYY			
Packaging:			
Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
10.5 kgs	350*260*350	500ft/Box	36