

**SCP PART#: 22/2ZIP-1000**

**DESCRIPTION:**

2C/22 AWG BC Unshielded, ZIP Cable (side x side construction), MultiPurpose, UL CMR PVC Jkt- White  
1000 Ft Box

Rev02/22

General Specification of Product :

Final Diameter :	0.140 inches	3.556 mm
Total Cable Weight :	8 kg/km	5 lbs/1000 ft
Conductor :	22 AWG 7 x .0097 Bare Copper	
Insulation :	PVC	

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/2ZIP - - - (UL) FPLR  
E324624-SCP 2/C 22 AWG - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9  
RoHS

Electrical Characteristics :

DC Resistance 25°C:	17.3 Ohms / 1000 ft
Mutual Capacitance :	13.6 pF/ft
Impedance :	120 Ohms
Velocity of Prop :	66 %
Inductance. :	1.3 mH/km

Additional Information :

Cabled OD Avg: None  
Ins Thickness: 0.020  
Jkt Thickness: None  
Certified: UL FPLR  
Flame Rating: Riser  
Max Voltage: 300V  
Packaging: Reelex Box 11.5 x 11.5 x 7.75"  
Packaged Weight: 4.5 kgs / 10 lbs

( All of the above values are approximated to within +/- 10% )

QMS Registered ISO 9001