



SPECIFICATION SHEET

www.scpcat5e.com
sales@scpcat5e.com

20-May-2014

Product Number : 22/4COIL-OR

RoHS

Description : 4C/22 AWG STRANDED PVC COIL PACK- ORANGE- 500 FT

Conductor : 22 AWG 7x.0097 Bare Copper	
Total Cable Weight : 22 kg/km	Final Diameter : 0.131 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 16.3 Ohms / 1000 ft	Mutual Capacitance : 23.3 pF/ft
Impedance : 80.6 Ohms	
Velocity of Prop : 64 %	Inductance. : 1.6 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/4 - - - (UL) CL3R E198137 (UL)
C(UL) CMR UNSH 4/C 22 AWG - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8
9 RoHS

Cabled OD Avg: 0.097	NEC Articles: 800, 725
Ins Thickness: 0.006	Min. Bend Radius/Minor Axis: .917 inches
Jkt Thickness: 0.015	Operating Temperature : -20°C to 60°C
Certified: UL CL3R/CMR	Standard UL Temp : 60°C
Flame Rating: Riser	
Max Voltage: 300V	

Packaging Weight : 7 lbs / 3.18 kgs

(All of the above values are approximated to within +/- 10%)

3072204.02R.1000