



Structured Cable Products

Quality Installations Deserve Quality Products

SPECIFICATION SHEET

Phone: 866-470-5742

sales@scpcat5e.com

www.scpcat5e.com

30-May-2014

Product Number : **22/12P**

RoHS

**Unsh Cable 12/C 22/7 AWG SBC
PVC PLENUM Insulation
White PVC PLENUM FT-6 Jacket
1000 FEET Plywood Spool**

Conductor : 22 AWG 7x.0097 Bare Copper	
Total Cable Weight : 57 kg/km	Final Diameter : 0.213 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 16 Ohms / 1000 ft	Mutual Capacitance : 23 pF /ft
Impedance : 68 Ohms	
Velocity of Prop : 62 %	Inductance. : 1.5 mH /km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 22/12P --- (UL) CL2P/CL3P
E132885 OR FPLP 75°C (UL) C(UL) CMP FT-6 UNSH 12/C 22 AWG ---
ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.150
Ins Thickness: 0.008
Jkt Thickness: 0.015
Certified: UL CL2P/CL3P OR FPLP/CMP
Flame Rating: Plenum
Max Voltage: 300V

(All of the above values are approximated to within +/- 10%)

7562212BPV6.02S.1000