



# Structured Cable Products

Quality Installations Deserve Quality Products

## SPECIFICATION SHEET

Phone: 866-470-5742

sales@scpcat5e.com

www.scpcat5e.com

30-May-2014

Product Number : **22/8P**

**RoHS**

**Station Z 8/C 22/7 AWG SBC  
PVC PLENUM Insulation  
White PVC PLENUM FT-6 Jacket  
1000 FEET Reelex**

Conductor : 22 AWG 7x.0097 Bare Copper	
Total Cable Weight : 48 kg/km	Final Diameter : 0.180 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 16 Ohms / 1000 ft	Mutual Capacitance : 22 pF /ft
Impedance : 70 Ohms	
Velocity of Prop : 58 %	Inductance. : 1.4 mH /km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 22/8P --- (UL) CL2P/CL3P E132885  
OR FPLP 75°C (UL) C(UL) CMP FT-6 UNSH 8/C 22 AWG --- ZONE/DEVICE A  
B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.110  
Ins Thickness: 0.008  
Jkt Thickness: 0.015  
Certified: UL CL2P/CL3P OR FPLP/CMP  
Flame Rating: Plenum  
Max Voltage: 300V

( All of the above values are approximated to within +/- 10% )

7562208BPV6.02R.1000