



Structured Cable Products
Quality Installations Deserve Quality Products

56Y4
E145249
ENCLOSURE
SCREW X 2 PCS (6#-32*25)
SCREW X 2 PCS (6#-32*8)

Scale	1:1	All Copy Rights Reserved	
3rd Angle Projection		REV DATE	9/27/2013 JENNIFER
Unit	mm	SCP PART #	
Date	2010/6/11		252
Tolerance			
~20	±0.2	~50	±0.5
~150	±1.5	150~	±1.5
ANGLE	±2°	ANGLE	±2°
Checked by	chialin	Drawn by	JENNIFER

MATERIAL
FACEPLATE : ABS HIGH-IMPACT UL94V-0 THERMOPLASTIC
SCREWS : SLOTTED PHILIPS CROSS RECESSED OVAL HEAD (COUNTERSUNK) 6#-32*25 WHITE PAINTED OVER NICKEL UNDERCOAT.
SLOTTED PHILIPS CROSS RECESSED OVAL HEAD (COUNTERSUNK) 6#-32*8 WHITE PAINTED OVER NICKEL UNDERCOAT.
BRUSH : PBT ULTRADUR® B 4500

PHYSICAL CHARACTERISTICS
OPERATING TEMPERATURE RANGE : -10°C TO 60°C.
STORAGE TEMPERATURE RANGE : -40°C TO 68°C.
HUMIDITY : 10%~90%RH.