



Structured Cable Products
Quality Installations Deserve Quality Products

56Y4
E145249
ENCLOSURE
SCREW X 2 PCS (6#-32*25)
SCREW X 2 PCS (6#-32*8)

MATERIAL		FACEPLATE : ABS HIGH-IMPACT UL94V-0 THERMOPLASTIC		SCREWS : SLOTTED PHILIPS CROSS RECESSED OVAL HEAD (COUNTERSUNK) 6#-32*25 WHITE PAINTED OVER NICKEL UNDERCOAT.		SLOTTED PHILIPS CROSS RECESSED OVAL HEAD (COUNTERSUNK) 6#-32*8 WHITE PAINTED OVER NICKEL UNDERCOAT.		BRUSH : PBT ULTRADUR® B 4500	
PHYSICAL CHARACTERISTICS		OPERATING TEMPERATURE RANGE : -10°C TO 60°C.		STORAGE TEMPERATURE RANGE : -40°C TO 68°C.		HUMIDITY : 10%-90%RH.			
Scale	1:1	All Copy Rights Reserved		REV DATE 9/27/2013		JENNIFER			
3rd Angle Projection				SCP PART #		253		Checked by	
Unit	mm			Drawn by		chialin			
Date	2010/6/11								
Tolerance		~20	±0.2	~50	±0.4	~150	±0.5	ANGLE	±2°