























KFY FFATURES

- Ultra HD 4K Video Transmission (upto 340Mhz), 1080p, 3D
- 8 x Input Modules
- 8 x Output Modules
- HDMI-CEC Bi-Directional Control
- · Bi-Directional IR Control
- · Responsive Web Interface
- · Automatic EDID Management
- · Three Year Standard Warranty
- · Control System Support





With MatrixOS you can control your matrix from any mobile device that is connected to the same network, simply by visiting www.gotomymatrix.com

HDBaseT LITE OR PRO

neo:8 Modular offers both HDBaseT Lite and Pro Transmitter modules, complete your choice with the appropriate neo Receiver - Lite for up to 70m or Pro for up to 100m.

BRITISH BUILT

Our neo systems are designed, built and supported at our head office in the UK. We pride ourselves on being British. Our highly trained assembly team allow you to trust the build quality of our systems. Our standard three year warranty is there should you ever need it giving you total peace of mind.


MATRIXOS

At the core of neo is MatrixOS the beating heart of our 340Mhz video processing unit. Providing you with instant access to all of your connected source devices in stunning Ultra HD 4K, 1080p or 3D. This powerhouse helps to create a "just works" solution, from dynamically generating EDIDs (to ensure the best video quality to every TV) right through to handling software updates for the HDBaseT link. With one goal in mind. Giving you the best possible video distribution system in the world.

CEC CONTROL

Additionally, MatrixOS allows installers to tap into the powerful capabilities of CEC control. HDMI-CEC triggers functions by communicating directly via the existing HDMI cable. No IR kit or cables are required with CEC, making for an easier and neater installation. Use CEC to change sources at a display using the TV's own remote and take advantage of Device OSD Name Transfer.





neo:8 MODUL AR MATRIX

Input Up to 8 Modules

8× IR Receiver

Output Up to 8× Modules

8× IR Emitter

(W) 43 cm / (H) 8.9 cm / (D) 41 cmDimensions

Weight 7kg +

HDBaseT™ RECEIVERS

Choice of Lite (70m) or Pro (100m)

Input Pro: 1x HDBaseT™ Class A (Pro)

Lite: 1x HDBaseT™ Class B (Lite)

Output 1x HDMI 2.0a



MODULES

HDMI INPUT/OUTPUT

Dimensions W 3.8 / H 3.8 / D 15cm

Weight 0.11 kg Input or Output 1x HDMI

HDMI 2.0A OUTPUT

Dimensions W 3.8 / H 3.8 / D 15cm

Weight 0.10 kg

1x HDMI 2.0a Output

HDMI 2.0A INPUT

W 3.8 / H 3.8 / D 15cm **Dimensions**

Weight 0.10 kg

Output 1x HDMI 2.0a

HDBaseT™ LITE OUTPUT

W 3.8 / H 3.8 / D 15cm Dimensions

Weight 0.10 kg

Output 1x HDBaseT™ Class B (Lite)

HDBaseT™ PRO INPUT

Dimensions W 3.8 / H 3.8 / D 15cm

Weight 0.10 kg

Output 1x HDBaseT™ Class A (Pro)

HDBaseT™ PRO OUTPUT

Dimensions W 3.8 / H 3.8 / D 15cm

Weight 0.10 kg

Output 1x HDBaseT™ Class A (Pro)

COMPATIBLE DRIVERS









TECHNICAL DATA

Dimensions (WxHxD):	43 cm / 8.9 cm / 41 cm
Weight:	7.3kg
Material:	Smooth textured powder coated steel
Operating Temperature Range:	0 to +35°C (32 to +95°F)
Operating Humidity Range:	5 to 90 % RH (no condensation)
Power Supply:	1 x IEC C14 Inlet - 100-240V 4.0/2.0A 50/60Hz
Power Consumption:	Max 2Amps @ 240V
Video Input:	Up to 8 Input Modules - HDMI or HDBaseT™ Class A (Pro)
Clock Speed:	Input: 340Mhz, Output: 340Mhz
Video Output:	Up to 8 input modules. HDMI, HDBaseT™ Class A (Pro) or HDBaseT™ Class B (Lite)
Color Supported:	4K/24bit, 1080p/36bit
3D Supported:	Up to 1080/24p - Frame packing/sequential (Blu-ray), Interlaced stereoscopic (satellite/cable broadcasts)
Additional:	HDMI 2.0a 3840 x 2160p 60Hz YCC 4:2:0 format pass-through
Encryption:	HDCP and HDCP 2.2 (with upgraded input module)
Supported Video Resolutions:	720p, 1080i, 1080p (+3D), 4k (30Hz) 4:4:4, 4k (50/60Hz) 4:2:0
Supported Audio Formats:	PCM 2.0, LPCM 2.0, LPCM 5.1, LPCM 6.1, LPCM 7.1, Dolby Digital 2.0, Dolby Digital 5.1, Dolby Digital EX 6.1, Dolby Digital Plus 7.1, Dolby TrueHD 5.1, Dolby TrueHD 7.1, Dolby Atmos 5.1.2, Dolby Atmos 5.1.4, Dolby Atmos 7.1.2, Dolby Atmos 7.1.4, Dolby Atmos 9.1.2, DTS 5.1, DTS-HD Master 5.1, DTS-HD Master 7.1, DTS 96/24 5.1, DTS-ES Discrete 6.1, DTS-ES Matrix 6.1
ESD Protection:	± 8kV (Air-gap discharge) ± 4 kV (Contact discharge)
Surge Protection:	IEC 61000-4-4 (EFT) 40A (5/50ns) IEC 61000-4-5 (Lightning) 25A (8/20μs)
Certification:	CE, FCC, RoHS

PULSE-EIGHT RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are for reference purposes only. All information discussed herein is provided on an "AS IS" basis, without warranties of any kind. This document and all information discussed herein remain the sole and exclusive property of Pulse-Eight Limited. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted by one party to the other party under this document, by implication, estoppel or otherwise. Pulse-Eight products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defence application, or any governmental procurement to which special terms or provisions may apply. All brand names, trademarks and registered trademarks belong to their respective owners.

© 2017 Pulse-Eight Limited. All rights reserved.

