

Coaxial Cables Line Card (USA Warehouses)



Structured Cable Products ("SCP") is a leading manufacturer and global supplier of low voltage cables and connectivity accessories. SCP cables provide the highest quality, performance and value on the market today. SCP offers a wide variety of cables and accessories to accommodate most commercial/residential installations. This Line Card contains our standard stock items for Coaxial cables available at our USA warehouses. We have many other bulk cables that may be available through our USA warehouses including Private Label and OEM.

SCP → **Structured Cable Products**[®]
 Quality Installations Deserve Quality Products
 Manufacturer and Global Supplier



RG6/U Quad Shield Coax

Features		Compliance		Applications		
Premium 75 Ohm 3.0GHz Tested Quad (4) Shield Coax, UL Listed, Sun Resistant Jkt; Descending FT and Zone/Outlet Jkt Markings		UL TYPE CATV CMP, CMR, CM c(UL); RoHS; NEC: CATV, CATVR, CMR, CM		Audio/Video, CATV, SATV, Antenna		
SCP Part Number	Construction	Nom. OD	Jacket / Color	Inst. Rating	Packaged Length	Weight
RG6/U Quad Shield Coax - Solid Bare Copper (BC):						
RG6/UQ-P-SPL	18AWG SOL BC F-FEP, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	6.7mm/0.264"	LS-UV-PVC	UL CMP/CL2P	305m/1000ft Spool	16kgs/35lbs
RG6/UQ-BC-BK	18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	UV-PVC - Black	UL CM	305m/1000ft Box	15.5kgs/34lbs
RG6/UQ-BC-BK-5	18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - Black	UL CM	152m/500ft Box	8kgs/17.6lbs
RG6/UQ-BC-BK-SPL	18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - Black	UL CM	305m/1000ft Spool	15.9kgs/35lbs
RG6/UQ-BC-WT	18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - White	UL CM	305m/1000ft Box	15.5kgs/34lbs
RG6/UQ-BC-WT-5	18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - White	UL CM	152m/500ft Box	8kgs/17.6lbs
RG6/UQ-BC-WT-SPL	18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - White	UL CM	305m/1000ft Spool	15.9kgs/35lbs
RG6/UQ-S-BC-BK	Dual Coax - Siamese: 2x 18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	15mm/0.59"	FR-PVC - Black	UL CM	152m/500ft Spool	16.2kgs/36lbs
RG6/UQ-S-BC-WT	Dual Coax - Siamese: 2x 18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	15mm/0.59"	FR-PVC - White	UL CM	152m/500ft Spool	16.2kgs/36lbs
RG6/U Quad Shield Coax - Solid Copper Clad Steel (CCS):						
RG6/UQ-CCS-BK-ETL-CMR	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.15mm/0.281"	FR-PVC - Black	ETL CMR	305m/1000ft Box	14.4kgs/32lbs
RG6/UQ-CCS-BK	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - Black	UL CM	305m/1000ft Box	15kgs/33lbs
RG6/UQ-CCS-BK-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - Black	UL CM	305m/1000ft Spool	15.5kgs/34lbs
RG6/U-CCS-BK-5	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - Black	UL CM	152m/500ft Box	8.5kgs/19lbs
RG6/UQ-CCS-BK-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.3mm/0.287"	FR-PVC - Black	ETL CM	305m/1000ft Box	15kgs/33lbs
RG6/UQ-CCS-BK-ETL-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.3mm/0.287"	FR-PVC - Black	ETL CM	305m/1000ft Spool	15.5kgs/34lbs
RG6/UQ-CCS-BK-5-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - Black	ETL CM	152m/500ft Box	8.5kgs/19lbs
RG6/UQ-CCS-WT	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - White	UL CM	305m/1000ft Box	15kgs/33lbs
RG6/UQ-CCS-WT-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - White	UL CM	305m/1000ft Spool	15.5kgs/34lbs
RG6/UQ-CCS-WT-5	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.2mm/0.283"	FR-PVC - White	UL CM	152m/500ft Box	8.5kgs/19lbs
RG6/UQ-CCS-WT-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.3mm/0.287"	FR-PVC - White	ETL CM	305m/1000ft Box	15kgs/33lbs
RG6/UQ-CCS-WT-SPL-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.3mm/0.287"	FR-PVC - White	ETL CM	305m/1000ft Spool	15.5kgs/34lbs
RG6/UQ-CCS-WT-5-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	7.3mm/0.287"	FR-PVC - White	ETL CM	152m/500ft Spool	8.5kgs/19lbs
RG6/UQ-S-CCS-BK	Dual Coax - Siamese: 2x 18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	15mm/0.59"	FR-PVC - Black	UL CM	305m/1000ft Spool	32kgs/71lbs
RG6/UQ-S-CCS-WT	Dual Coax - Siamese: 2x 18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%	15mm/0.59"	FR-PVC - White	UL CM	305m/1000ft Spool	32kgs/71lbs

RG6/U Dual Shield Coax

Features		Compliance		Applications		
Premium 75 Ohm 3.0GHz Tested Dual Shield Coax, Solid Bare Copper Conductor, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings		UL TYPE CATV c(UL) CM; RoHS		Audio/Video, CATV, CCTV transmission		
SCP Part Number	Construction	Nom. OD	Jacket / Color	Inst. Rating	Packaged Length	Weight
RG6/U Dual Shield Coax - Solid Bare Copper (BC):						
RG6/U-BC-BK	18AWG SOL BC FPE, Bonded CU Foil, 60% AL Braid	6.8mm	FR-PVC - Black	UL CM	305m/1000ft Box	14kgs/31lbs
RG6/U-BC-BK-5	18AWG SOL BC FPE, Bonded CU Foil, 60% AL Braid	6.8mm	FR-PVC - Black	UL CM	152m/500ft Box	7.3kgs/16lbs
RG6/U-BC-WT	18AWG SOL BC FPE, Bonded CU Foil, 60% AL Braid	6.8mm	FR-PVC - White	UL CM	305m/1000ft Box	14kgs/31lbs
RG6/U-BC-WT-5	18AWG SOL BC FPE, Bonded CU Foil, 60% AL Braid	6.8mm	FR-PVC - White	UL CM	152m/500ft Box	7.3kgs/16lbs
RG6/U-BC-MES	18AWG SOL BC FPE, Bonded CU Foil, 60% AL Braid + Messenger	19mm/0.75"	FR-PVC - Black	UL CM	152m/500ft Reel in Box	10.7kgs/24lbs
RG6/U-S-BC-BK	Dual Coax - Siamese: 2x 18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60%	21.3mm/0.84"	FR-PVC - Black	UL CM	152m/500ft Reel in Box	14.9kgs/33lbs
RG6/U Dual Shield Coax - Solid Copper Clad Steel (CCS):						
RG6/U-P	18AWG SOL CCS F-FEP, Bonded AL Foil + AL Braid 60%	5.9mm/0.232"	LS-PVC	UL CMP/CL2P	305m/1000ft Spool	26kgs/57lbs
RG6/U-CCS-BK	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.8mm/0.268"	FR-PVC - Black	UL CM	305m/1000ft Box	13.8kgs/30lbs
RG6/U-CCS-BK-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.91mm/0.272"	FR-PVC - Black	UL CM	305m/1000ft Spool	12.7kgs/28lbs
RG6/U-CCS-BK-5	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.91mm/0.272"	FR-PVC - Black	UL CM	152m/500ft Box	7.1kgs/16lbs
RG6/U-CCS-BK-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.8mm/0.268"	FR-PVC - Black	ETL CM	305m/1000ft Box	12.1kgs/27lbs
RG6/U-CCS-BK-ETL-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.91mm/0.272"	FR-PVC - Black	ETL CM	305m/1000ft Spool	12.9kgs/28.5lbs
RG6/U-CCS-BK-5-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.91mm/0.272"	FR-PVC - Black	ETL CM	152m/500ft Box	6.5kgs/14lbs
RG6/U-CCS-WT	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.8mm/0.268"	FR-PVC - White	UL CM	305m/1000ft Box	13.8kgs/30lbs
RG6/U-CCS-WT-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.91mm/0.272"	FR-PVC - White	UL CM	305m/1000ft Spool	12.7kgs/28lbs
RG6/U-CCS-WT-5	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.91mm/0.272"	FR-PVC - White	UL CM	152m/500ft Box	7.1kgs/16lbs
RG6/U-CCS-WT-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.8mm/0.268"	FR-PVC - White	ETL CM	305m/1000ft Box	12.1kgs/27lbs
RG6/U-CCS-WT-ETL-SPL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.8mm/0.268"	FR-PVC - White	ETL CM	305m/1000ft Spool	12.9kgs/28.5lbs
RG6/U-CCS-WT-5-ETL	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	6.8mm/0.268"	FR-PVC - White	ETL CM	152m/500ft Box	6.5kgs/14lbs
RG6/U-S-CCS-BK-RIB	Dual Coax - Siamese: 2x 18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%	21.3mm/0.84"	FR-PVC - Black	UL CM	152m/500ft Reel in Box	14.2kgs/31lbs

RG6/U Tri Shield Coax

Features		Compliance		Applications		
Premium 75 Ohm 3.0GHz Tested Tri Shield Coax, Solid Bare Copper Conductor, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings		UL TYPE CATV c(UL) CM; RoHS		Audio/Video, CATV		
SCP Part Number	Construction	Nom. OD	Jacket / Color	Inst. Rating	Packaged Length	Weight
RG6/U-T-CCS-WT-500	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil	7.06mm/0.278"	FR-PVC - Black	UL CM	152m/500ft Reel in Box	7.9kgs/17.5lbs

RG6/U 95% Coax

Features		Compliance		Applications		
Premium 75 Ohm 3.0GHz Tested Coax, Solid Bare Copper Conductor, 95% BC Braid Shield, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings		UL TYPE CATV c(UL) CM; RoHS		CCTV transmission, Audio/Video		
SCP Part Number	Construction	Nom. OD	Jacket / Color	Inst. Rating	Packaged Length	Weight
RG6/U95-BK	18AWG SOL BC FPE, 95% BC Braid	6.91mm/0.272"	FR-PVC - Black	UL CM	305m/1000ft Box	15kgs/33lbs
RG6/U95-S-BK	18AWG SOL BC FPE, 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese	19mm/0.75"	FR-PVC - Black	UL CM	305m/1000ft Spool	23.1kgs/51lbs
RG6/U95-S-BK-500	18AWG SOL BC FPE, 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese	19mm/0.75"	FR-PVC - Black	UL CM	152m/500ft Reel in Box	10kgs/22lbs

RG11/U Coax

Features		Compliance		Applications		
Premium 75 Ohm 3.0GHz Tested Coax, Solid Bare Copper Conductor, 95% BC Braid Shield, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings		UL TYPE CATV c(UL) CM; RoHS		CCTV transmission, Audio/Video		
SCP Part Number	Construction	Nom. OD	Jacket / Color	Inst. Rating	Packaged Length	Weight
RG11/U	14AWG SOL CCS FPE, Bonded AL Foil, 60% AL Braid	10mm/0.395"	FR-PVC - Black	UL CM	305m/1000ft Spool	26.5kgs/58.5lbs
RG11/U-DB	14AWG SOL CCS FPE, Bonded AL Foil, 60% AL Braid, Gel Fill	10mm/0.395"	PE - Black	Direct Burial/Outdoor	305m/1000ft Reel in Box	27.5kgs/61lbs

RG59/U Coax

Features		Compliance		Applications		
75 Ohm CCTV Coax Cable, Solid Bare Copper Conductor, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings		UL TYPE CATV c(UL) CM; RoHS		Audio/Video, CCTV transmission		
SCP Part Number	Construction	Nom. OD	Jacket / Color	Inst. Rating	Packaged Length	Weight
RG59/U 95% BC Braid - Nonplenum:						
RG59/U95-BK	20 AWG SOL BC SFPE, 95% BC Braid	6.0mm/0.236"	FR-PVC - Black	UL CM	305m/1000ft Reel in Box	14.9kgs/33lbs
RG59/U95-BK-500	20 AWG SOL BC SFPE, 95% BC Braid	6.0mm/0.236"	FR-PVC - Black	UL CM	152m/500ft Box	
RG59/U95-WT	20 AWG SOL BC SFPE, 95% BC Braid	6.0mm/0.236"	FR-PVC - White	UL CM	305m/1000ft Reel in Box	14.9kgs/33lbs
RG59/U95-S-BK	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese	16.9mm/0.664"	FR-PVC - Black	UL CM	305m/1000ft Spool	23.2kgs/51lbs
RG59/U95-S-BK-5	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese	16.9mm/0.664"	FR-PVC - Black	UL CM	152m/500ft Spool	11.4kgs/25lbs
RG59/U95-S-BK-5-RIB	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese	16.9mm/0.664"	FR-PVC - Black	UL CM	152m/500ft Reel in Box	12.8kgs/28lbs
RG59/U95-S-WT	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese	16.9mm/0.664"	FR-PVC - White	UL CM	305m/1000ft Spool	23.2kgs/51lbs
RG59/U95-S-WT-5	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese	16.9mm/0.664"	FR-PVC - White	UL CM	152m/500ft Spool	11.4kgs/25lbs
RG59/U95-S-WT-5-RIB	20 AWG SOL BC SFPE 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese	16.9mm/0.664"	FR-PVC - White	UL CM	152m/500ft Reel in Box	12.8kgs/28lbs
RG59/U Dual Copper Shield - Plenum:						
RG59/U95-P	20 AWG SOL BC F-FEP, 95% BC Braid	5.0mm/0.196"	LS-PVC - White	UL CMP/CL2P	305m/1000ft Spool	12kgs/26.5lbs
RG59/U95-S-P	20 AWG SOL BC F-FEP 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese	13.7mm/0.54"	LS-PVC - White	UL CMP/CL2P	305m/1000ft Spool	20.9kgs/46lbs
RG59/U95-S-P-500	20 AWG SOL BC F-FEP 95% BC Braid + Pwr: 2C/18AWG Str BC, Siamese	13.7mm/0.54"	LS-PVC - White	UL CMP/CL2P	152m/500ft Spool	10.5kgs/23lbs
RG59/U Dual Copper Shield - Direct Burial:						
RG59/U95-DB	20 AWG SOL BC SFPE, 95% BC Braid	6.0mm/0.236"	PE - Black	Direct Burial/Outdoor	305m/1000ft Spool	12.9kgs/28lbs
RG59/U CCA Braid - Nonplenum:						
RG59/U-CCA-BK-RIB	20 AWG BC SFPE, 95% CCA BRAID	6.0mm/0.236"	FR-PVC - Black	UL CM	305m/1000ft Reel in Box	12.5kgs/27.5lbs
RG59/U-CCA-BK-5-RIB	20 AWG BC SFPE, 95% CCA BRAID	6.0mm/0.236"	FR-PVC - Black	UL CM	152m/500ft Reel in Box	6.6kgs/14.5lbs
RG59/U-CCA-WT-5-RIB	20 AWG BC SFPE, 95% CCA BRAID	6.0mm/0.236"	FR-PVC - White	UL CM	152m/500ft Reel in Box	6.6kgs/14.5lbs
RG59/U-S-CCA-BK	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	16.9mm/0.664"	FR-PVC - Black	UL CM	305m/1000ft Spool	19.7kgs/43.5lbs
RG59/U-S-CCA-BK-5	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	16.9mm/0.664"	FR-PVC - Black	UL CM	152m/500ft Spool	10.2kgs/22.5lbs
RG59/U-S-CCA-BK-5-RIB	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	16.9mm/0.664"	FR-PVC - Black	UL CM	152m/500ft Reel in Box	10.2kgs/22.5lbs
RG59/U-S-CCA-WT	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	16.9mm/0.664"	FR-PVC - White	UL CM	305m/1000ft Spool	19.7kgs/43.5lbs
RG59/U-S-CCA-WT-5	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	16.9mm/0.664"	FR-PVC - White	UL CM	152m/500ft Spool	10.2kgs/22.5lbs
RG59/U-S-CCA-WT-5-RIB	20 AWG SOL BC SFPE, 95% CCA Braid + Pwr: 2C/18AWG Str BC	16.9mm/0.664"	FR-PVC - White	UL CM	152m/500ft Reel in Box	10.2kgs/22.5lbs
RG59/U CCA Braid - Direct Burial:						
RG59/U-S-DB	20 AWG SOL BC SFPE, 95% CCA Braid, Gel Fill + Pwr: 2C/18AWG Str BC, Siamese	16.9mm/0.664"	PE - Black	Direct Burial/Outdoor	305m/1000ft Spool	20.4kgs/45lbs
RG59/U-S-DB-500	20 AWG SOL BC SFPE, 95% CCA Braid, Gel Fill + Pwr: 2C/18AWG Str BC, Siamese	16.9mm/0.664"	PE - Black	Direct Burial/Outdoor	152m/500ft Spool	12.2kgs/27lbs

Direct Burial Coax

Features		Compliance		Applications		
Premium 75 Ohm 3.0GHz Tested Quad (4) Shield Coax, UL Listed, Descending M/FT and Zone/Outlet Jkt Markings		UL CM; EN50575 CPR Compliant; RoHS		Audio/Video, CATV, SATV, Antenna		
SCP Part Number	Construction	Nom. OD	Jacket / Color	Inst. Rating	Packaged Length	Weight
RG6/UQ-DB	18AWG SOL BC FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%, Gel Filled	7.54mm/0.297"	PE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	13.5kgs/30lbs
RG6/UQ-DB-CCS	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60% + AL Foil + AL Braid 40%, Gel Filled	7.54mm/0.297"	PE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	13.5kgs/30lbs
RG6/U-DB	18AWG SOL CCS FPE, Bonded AL Foil + AL Braid 60%, Gel Filled	6.91mm/0.272"	PE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	11.5kgs/25lbs
RG11/U-DB	14AWG SOL CCS FPE, Bonded AL Foil, 60% AL Braid, Gel Fill	10mm/0.395"	PE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	27.5kgs/61lbs

All weights and dimensions are approximate and every effort has been made to ensure its accuracy at time of publication. The information herein is subject to change without notice.

Private Label & OEM Services

SCP is a manufacturer and product developer. SCP is an industry leader in cable and connectivity development. Are you interested in private label or OEM services for bulk cables or connectivity solutions? Private Label can differentiate your brand from the competition and improves customer retention. Let us know what your needs are to see if Private Label or OEM services is a better solution for you.

For more information contact us at:
sales@scpcat5e.com | Phone: +1 (954) 327-5770

SCP Corporate Office:
 3490 SW 30th Ave, Dania Beach, FL 33312, USA

