## **Direct Burial Cables Line Card (USA Warehouses)**















## Landscape / Direct Burial ProSeries Speaker Cables

Professionals Choice for All High Performance Landscape and Outdoor Speaker Systems. Retains Flexibility in All Outdoor Environments. SCP ProSeries Landscape/Direct Burial cables feature LLDPE (Linear Low-Density Polyethelene) jackets that provide superior performance and durability over PVC or standard PE jacket cables. These cables also are UV Sun Resistant and retains flexible performance in both hot and cold environments. Recommended by Leading Speaker Brands.

Features			Compliance		Applications			
High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair; LLDPE Jacket; Waterproof: Gel Filled; Superior Durability and Longevity; Rodent Resistant; UV Sun Resistant; Descending Feet Markings		UL 444, NEC CL3, RoHS		Professional Outdoor Speaker Systems; Direct Burial Waterproof; Audio/Security/Control; Class 2/3 Low Voltage Power; Installs in Wet Environments; Commercial/Residential/Institutional				
SCP Part Number	AWG	Conductors	Nom. OD mm/inch	CAP pF/FT	Installation Rated	Packaged Length	Weight	
14/2SP-DB-500	14	2/105 Str 0FC	6.4mm/0.252"	Gel Fill LLDPE - Black	Direct Burial/UV Outdoor	152m/500ft Spool	11.7kgs/26lbs	
14/4SP-DB-GEL	14	4/105 Str OFC	8.2mm/0.323"	Gel Fill LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	40kgs/88lbs	
14/4SP-DB-GEL-500	14	4/105 Str OFC	8.2mm/0.323"	Gel Fill LLDPE - Black	Direct Burial/UV Outdoor	152m/500ft Spool	21kgs/46lbs	

Direct Burial Multipurpose Security, Audio/Sound, Control									
Features				Compliance		Applications			
LLDPE jacket superior to PVC jacket direct burial. Insulated Twisted Pair; Water Block Tape for moisture protection; Descending Feet and Zone/Outlet Jkt Markings ; Packaging: Spool			UL 444, NEC CL3, RoHS		Direct Burial; Outdoor; Outdoor Speaker; Low Voltage Class 2/3, Security Systems; Intercom Systems; Speaker/Audio Systems; Power-Limited Controls				
Direct Burial - UnShielded									
SCP Part Number	AWG	Conductors	Nom. OD mm/inch	CAP pF/FT	Installation Rated	Packaged Length	Weight		
18/2DB-500	18	2/16 STR BC	5.2mm/0.204"	WBT LLDPE-Black	Direct Burial/UV Outdoor	152m/500ft Spool	5.8kgs/13lbs		
16/2DB	16	2/65 STR BC	5.5mm/0.215"	WBT LLDPE-Black	Direct Burial/UV Outdoor	305m/1000ft Spool	14.6kgs/32lbs		
16/4DB	16	4/65 STR BC	6.8mm/0.267"	WBT LLDPE-Black	Direct Burial/UV Outdoor	305m/1000ft Spool	25kgs/55lbs		
16/4DB-500	16	4/65 STR BC	6.8mm/0.267"	WBT LLDPE-Black	Direct Burial/UV Outdoor	152m/500ft Spool	12.2kgs/27lbs		
14/4DB	14	4/105 STR BC	8.2mm/0.322"	WBT LLDPE-Black	Direct Burial/UV Outdoor	305m/1000ft Spool	39kg/76lbs		
14/4DB-500	14	4/105 STR BC	8.2mm/0.322"	WBT LLDPE-Black	Direct Burial/UV Outdoor	152m/500ft Spool	19.5kg/43lbs		
			Direct B	urial - Shielded					
SCP Part Number	AWG	Conductors	Nom. OD mm/inch	CAP pF/FT	Installation Rated	Packaged Length	Weight		
18/2SHDB	18	2/16 STR BC	5.4mm/0.212"	WBT LLDPE-Black	Direct Burial/UV Outdoor	305m/1000ft Spool	12kgs/26lbs		
18/4SHDB	18	2/16 STR BC	6.2mm/0.244"	WBT LLDPE-Black	Direct Burial/UV Outdoor	305m/1000ft Spool	18.5kgs/41lbs		
18/6SHDB	18	2/16 STR BC	7.2mm/0.283"	WBT LLDPE-Black	Direct Burial/UV Outdoor	305m/1000ft Spool	24.7kgs/54lbs		
16/2SHDB	16	2/65 STR BC	6.3mm/0.248"	WBT LLDPE-Black	Direct Burial/UV Outdoor	305m/1000ft Spool	16kgs/35lbs		
16/2SHDB-500	16	2/65 STR BC	6.3mm/0.248"	WBT LLDPE-Black	Direct Burial/UV Outdoor	152m/500ft Spool	8.5kgs/19lbs		
14/2SHDB	14	2/105 STR BC	7.2mm/0.283"	WBT LLDPE-Black	Direct Burial/UV Outdoor	305m/1000ft Spool	20.6kgs/45lbs		
14/2SHDB-500	14	2/105 STR BC	7.2mm/0.283"	WBT LLDPE-Black	Direct Burial/UV Outdoor	152m/500ft Spool	10.7kgs/24lbs		
12/2SHDB	12	2/65 STR BC	8.5mm/0.334"	WBT LLDPE-Black	Direct Burial/UV Outdoor	305m/1000ft Spool	32.5kgs/72lbs		

## Category/LAN Direct Burial

SCP Cat6 Direct Burial cables feature LLDPE (Linear Low-Density Polyethelene) jackets that provide superior performance over PVC or standard PE jacket cables. These cables also are UV Sun Resistant and retain flexible performance in both hot and cold environments.

Features			Compliance		Applications			
LLDPE Jacket, Moisture Protection and UV Sun Resistant; Descending FT and Zone/ Outlet Jkt Markings; Limited Lifetime Warranty		ANSI/TIA 568.2-D; ISO/IEC 11801; IEEE 802.3bt; RoHS		High performance IT, LAN & Ethernet installations. Suitable for use in all outdoor and direct burial structured wiring systems according to cable classification. PoE Compliant				
SCP Part Number	AWG	Conductors/Insulation	Nom. OD mm/inch	CAP pF/FT	Installation Rated	Packaged Length	Weight	
Cat6a:								
CAT6A-U/FTP-DB	4pr U/FTP	23AWG SOL BC / SFPE	7.4mm/0.291"	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	17kgs/38lbs	
Cat6:								
CAT6-DB	4pr U/UTP	23AWG SOL BC / HDPE	7.0mm/0.275"	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	16kgs/35lbs	
CAT6SH-DB	4pr F/UTP	23AWG SOL BC / HDPE	7.50mm/0.295"	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	19kgs/42lbs	
CAT6SH-OUT	4pr F/UTP	23AWG SOL BC / HDPE	7.50mm/0.295"	UV Sun Res PE - Black	UV Outdoor	305m/1000ft Spool	21kgs/46lbs	
Cat5e:								
CAT5E-25PR-DB	25pr U/UTP Gel	24AWG SOL BC / HDPE	12.0mm/0.472"	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	66.7kgs/147lbs	
CAT5E-DB	4pr U/UTP	24AWG SOL BC / HDPE	5.3mm/0.208"	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	10kgs/22lbs	
CAT5E-DB-500	4pr U/UTP	24AWG SOL BC / HDPE	5.3mm/0.208"	LLDPE - Black	Direct Burial/UV Outdoor	152m/500ft Spool	5.3kgs/12lbs	
CAT5E-SH-DB	4pr F/UTP	24AWG SOL BC / HDPE	6.5mm/0.256"	LLDPE - Black	Direct Burial/UV Outdoor	305m/1000ft Spool	15.8kgs/35lbs	

All weights and dimensions are approximate and every effort has been made to ensure its accuracy at time of publication. The information herein is subject to change without notice.



For more information contact us at: sales@scpcat5e.com | Phone: +1 (954) 327-5770 SCP Corporate Office: 3490 SW 30th Ave, Dania Beach, FL 33312, USA Rev. 02/22