


Multi-Purpose - Audio, Communication & Control Cables Line Card



Structured Cable Products ("SCP") is a leading manufacturer and global supplier of low voltage cables and connectivity accessories. SCP cables provide the highest quality, performance and value on the market today. SCP offers a wide variety of cables and accessories to accommodate most commercial/residential installations. This Line Card contains our standard stock items for Multi-Purpose Audio/Sound, Communication & Control cables available at our USA warehouses. We have many other bulk cables that may be available through our USA warehouses including Private Label and OEM.

SCP **Structured Cable Products®**
Quality Installations Deserve Quality Products
Manufacturer and Global Supplier



Analog Audio Cables

Features		Compliance		Applications		
Balanced line level audio and control. Superior signal-to-noise ratio. Riser rated. Descending FT and Zone/Outlet Jkt Markings. SCP Tangle-Free Reellex II Box.		UL CMR CL2R/CL3R, c(UL) FT4; RoHS; Low Voltage & Power Limited Systems; 300V 75°C		High performing audio and control distribution. Permanent or Semi-Permanent Installations. Microphone/Intercom Distribution. Sound/Audio Systems. Security and Power-Limited Control Controls.		
SCP Part Number	Construction	Nom. OD	CAP pF/FT	Jacket / Color	Packaged Length	Weight
22/2ESH	2C/22AWG BC Str Twisted Pair w/Drain, Shielded	3.4mm/0.134"	PVC - Gray	UL CMR	305m/1000ft Box	6.5kgs/14lbs
22/4EPSH	(2) Pair 22AWG BC Str Twisted Pair w/Drain, Each Pair Shielded	4.3mm/0.169"	PVC - Gray	UL CMR	305m/1000ft Box	10.9kgs/24lbs

Multi-Purpose Non-Plenum

Features			Compliance		Applications		
Stranded or Solid Bare Copper Conductors, Insulated Twisted Pair; UL Listed; Descending Feet and Zone/Outlet Jkt Markings; Packaging: Spool, Box			UL CMR CL2R/CL3R, c(UL) FT4; UL 444; NEC 725, 800; RoHS; Low Voltage & Power Limited Systems; 300V 75°C		Low Voltage Security & Control; Intercom Systems; Sound/Audio Systems; 70V Speaker; Power-Limited Controls Class 2 and Class 3		
Non-Plenum - Riser Unshielded							
SCP Part Number	AWG	Conductors	Nom. OD mm/inch	CAP pF/FT	Jacket / Color	Packaged Length	Weight
18/2-GY	18	2/16 STR BC	4.4mm/0.16"	20	PVC - Gray	305m/1000ft Box	9.5kgs/21lbs
18/2-GY-500	18	2/16 STR BC	4.4mm/0.16"	20	PVC - Gray	152m/500ft Box	4.6kgs/10.3lbs
18/2-WT	18	2/16 STR BC	4.4mm/0.16"	20	PVC - White	305m/1000ft Box	9.5kgs/21lbs
18/2-WT-500	18	2/16 STR BC	4.4mm/0.16"	20	PVC - White	152m/500ft Box	4.6kgs/10.3lbs
18/4-GY	18	4/16 STR BC	5.1mm/0.192"	23	PVC - Gray	305m/1000ft Box	14.5kgs/32lbs
18/4-GY-500	18	4/16 STR BC	5.1mm/0.192"	23	PVC - Gray	152m/500ft Box	8.2kgs/18lbs
18/4-WT	18	4/16 STR BC	5.1mm/0.192"	23	PVC - White	305m/1000ft Box	15.9kgs/35lbs
18/4-WT-500	18	4/16 STR BC	5.1mm/0.192"	23	PVC - White	152m/500ft Box	8.2kgs/18lbs
18/6-GY	18	6/16 STR BC	5.6mm/0.221"	21	PVC - Gray	305m/1000ft Spool	25kgs/55lbs
18/6-GY-500	18	6/16 STR BC	5.6mm/0.221"	21	PVC - Gray	152m/500ft Box	12.2kgs/27lbs
16/2-GY	16	2/26 STR BC	5.1mm/0.20"	23	PVC - Gray	305m/1000ft Box	13.1kgs/29lbs
16/4-GY	16	4/26 STR BC	5.9mm/0.234"	39	PVC - Gray	305m/1000ft Box	26kgs/57lbs
14/2-GY	14	2/19STR BC	5.6mm/0.221"	25	PVC - Gray	305m/1000ft Spool	18.1kgs/40lbs
14/4-GY	14	4/19 STR BC	6.78mm/0.267"	22	PVC - Gray	305m/1000ft Spool	33kgs/73lbs
Non-Plenum - Riser Shielded							
SCP Part Number	AWG	Conductors STR/SOL	Nom. OD mm/inch	CAP pF/FT	Jacket / Color	Packaged Length	Weight
22/2SH-GY	22	2/7 STR BC	3.0mm/0.118"	35	PVC - Gray	305m/1000ft Box	4.7kgs/10.5lbs
22/4SH-GY	22	4/7 STR BC	3.38mm/0.133"	42	PVC - Gray	305m/1000ft Box	7.5kgs/16.5lbs
22/4SH-GY-500	22	4/7 STR BC	3.38mm/0.133"	42	PVC - Gray	152m/500ft Box	3.9kgs/8.5lbs
22/6SH-GY	22	6/7 STR BC	3.81mm/0.15"	55	PVC - Gray	305m/1000ft Box	14kgs/31lbs
22/6SH-500	22	6/7 STR BC	3.81mm/0.15"	55	PVC - Gray	152m/500ft Box	6.8kgs/15lbs
22/6SH-WT	22	6/7 STR BC	3.81mm/0.15"	55	PVC - Gray	305m/1000ft Box	14kgs/31lbs
22/8SH-GY	22	8/7 STR BC	4.19mm/0.165"	39	PVC - Gray	305m/1000ft Box	14.7kgs/32.5lbs
22/8SH-WT	22	8/7 STR BC	4.19mm/0.165"	39	PVC - Gray	305m/1000ft Box	14.7kgs/32.5lbs
18/2SH-GY	18	2/16 STR BC	4.2mm/0.166"	69	PVC - Gray	305m/1000ft Box	11.8kgs/26lbs
18/4SH-GY	18	4/16 STR BC	5.5mm/0.2165"	130	PVC - Gray	305m/1000ft Spool	18.1kgs/40lbs
18/4SH-GY-500	18	4/16 STR BC	5.5mm/0.2165"	130	PVC - Gray	152m/500ft Box	9.5kgs/21lbs
18/6SH-GY	18	6/16 STR BC	5.6mm/0.221"	44	PVC - Gray	305m/1000ft Spool	21.8kgs/48lbs
18/6SH-GY-500	18	6/16 STR BC	5.6mm/0.221"	44	PVC - Gray	152m/500ft Box	10.9kgs/24lbs
18/8SH-GY	18	8/16 STR BC	6.35mm/0.25"	42	PVC - Gray	305m/1000ft Spool	27.6kgs/61lbs
16/2SH-GY	16	2/26 STR BC	5.13mm/0.202"	68	PVC - Gray	305m/1000ft Box	14.5kgs/32lbs
16/4SH-GY	16	4/26 STR BC	5.99mm/0.236"	51	PVC - Gray	305m/1000ft Spool	26.3kgs/58lbs
14/2SH-GY	14	2/19 STR BC	5.76mm/0.227"	65	PVC - Gray	305m/1000ft Spool	19kgs/42lbs
14/4SH-GY	14	4/19 STR BC	6.78mm/0.267"	74	PVC - Gray	305m/1000ft Spool	33.8kgs/70lbs

Rev. 02/22

Multi-Purpose Plenum

Features			Compliance		Applications		
Stranded or Solid Bare Copper Conductors, Insulated Twisted Pair; UL Listed; Descending Feet and Zone/Outlet Jkt Markings; Packaging: Spool or Box			UL CMP CL2P/CL3P, c(UL) FT6; UL 444; RoHS; Low Voltage & Power Limited Systems; 300V 75°C; 14-12AWG are not recognized by c(UL).		Low Voltage Security & Control; Intercom Systems; Sound/Audio Systems; 70V Speaker; Power-Limited Controls Class 2 and Class 3		
Plenum - Unshielded							
SCP Part Number	AWG	Conductors STR/SOL	Nom. OD mm/inch	CAP pF/FT	Jacket / Color	Packaged Length	Weight
22/2P	22	2/7 STR BC	3.0mm/0.12"	18	LS-PVC/White	305m/1000ft Box	4.5kgs/10lbs
22/4P	22	4/7 STR BC	3.58mm/0.141"	23	LS-PVC/White	305m/1000ft Box	7.2kgs/16lbs
22/4P-500	22	4/7 STR BC	3.58mm/0.141"	23	LS-PVC/White	152m/500ft Box	3.9kgs/8.5lbs
22/6P	22	6/7 STR BC	4.06mm/0.16"	21	LS-PVC/White	305m/1000ft Spool	10.2kgs/22.5lbs
22/6P-500	22	6/7 STR BC	4.06mm/0.16"	21	LS-PVC/White	152m/500ft Box	5.4kgs/12lbs
22/12P	22	12/7 STR BC	5.4mm/0.213"	23	LS-PVC/White	305m/1000ft Spool	20.8kgs/46lbs
18/2P	18	2/7 STR BC	4.16mm/0.164"	22	LS-PVC/White	305m/1000ft Spool	8.1kgs/18lbs
18/2P-500	18	2/7 STR BC	4.16mm/0.164"	22	LS-PVC/White	152m/500ft Box	4.3kgs/9.5lbs
18/4P	18	4/7STR BC	4.67mm/0.184"	28	LS-PVC/White	305m/1000ft Spool	18.1kgs/40lbs
18/4P-500	18	4/7 STR BC	4.67mm/0.184"	28	LS-PVC/White	152m/500ft Box	8.6kgs/19lbs
18/6P	18	6/7 STR BC	5.3mm/0.21"	28	LS-PVC/White	305m/1000ft Spool	25.4kgs/56lbs
18/8P	18	8/7 STR BC	6.0mm/0.238"	45	LS-PVC/White	305m/1000ft Spool	29.9kgs/66lbs
16/2P	16	2/19 STR BC	4.83mm/0.19"	24	LS-PVC/White	305m/1000ft Spool	20.4kgs/45lbs
16/2P-BK	16	2/19 STR BC	4.83mm/0.19"	24	LS-PVC/Black	305m/1000ft Spool	15kgs/33lbs
16/4P	16	4/19 STR BC	5.6mm/0.221"	26	LS-PVC/White	305m/1000ft Spool	26.7kgs/59lbs
16/4P-BK	16	4/19 STR BC	5.6mm/0.221"	26	LS-PVC/Black	305m/1000ft Spool	26.7kgs/59lbs
14/2P	14	2/19 STR BC	5.84mm/0.23"	22	LS-PVC/White	305m/1000ft Spool	18.1kgs/40lbs
14/2P-500-BOX	14	2/19 STR BC	5.84mm/0.23"	22	LS-PVC/White	152m/500ft Box	9.3kgs/20.5lbs
14/4P	14	4/19 STR BC	6.98mm/0.275"	25	LS-PVC/White	305m/1000ft Spool	33.6kgs/74lbs
14/4P-BK	14	4/19 STR BC	6.98mm/0.275"	25	LS-PVC/White	305m/1000ft Spool	33.6kgs/74lbs
12/2P	12	2/19 STR BC	6.98mm/0.275"	42	LS-PVC/White	305m/1000ft Spool	25.4kgs/56lbs
Plenum - Shielded							
SCP Part Number	AWG	Conductors STR/SOL	Nom. OD mm/inch	CAP pF/FT	Jacket / Color	Packaged Length	Weight
22/2SHP	22	2/7 STR BC	3.15mm/0.124"	49	LS-PVC/White	305m/1000ft Spool	5.2kgs/11.5lbs
22/4SHP	22	4/7 STR BC	3.93mm/0.155"	49	LS-PVC/White	305m/1000ft Spool	7.7kgs/17lbs
22/4SHP-500	22	4/7 STR BC	3.93mm/0.155"	49	LS-PVC/White	152m/500ft Box	5kgs/11lbs
22/6SHP	22	6/7 STR BC	4.11mm/0.162"	42	LS-PVC/White	305m/1000ft Spool	10.9kgs/24lbs
22/6SHP-500	22	6/7 STR BC	4.11mm/0.162"	42	LS-PVC/White	152m/500ft Box	5.4kgs/12lbs
18/2SHP	18	2/7 STR BC	0.16"	77	LS-PVC/White	305m/1000ft Spool	10.4kgs/23lbs
18/4SHP	18	4/7 STR BC	0.19"	53	LS-PVC/White	305m/1000ft Spool	16.8kgs/37lbs
18/4SHP-500	18	4/7 STR BC	0.19"	53	LS-PVC/White	152m/500ft Box	8.1kgs/18lbs
18/6SHP	18	6/7 STR BC	0.216"	42	LS-PVC/White	305m/1000ft Spool	25.4kgs/56lbs
18/8SHP	18	8/7 STR BC	0.24"	42	LS-PVC/White	305m/1000ft Spool	29.9kgs/66lbs
16/2SHP	16	2/19 STR BC	4.7mm/0.186"	59	LS-PVC/White	305m/1000ft Spool	13.1kgs/29lbs

All weights and dimensions are approximate and every effort has been made to ensure its accuracy at time of publication. The information herein is subject to change without notice.



Private Label & OEM Services

SCP is a manufacturer and product developer. SCP is an industry leader in cable and connectivity development. Are you interested in private label or OEM services for bulk cables or connectivity solutions? Private Label can differentiate your brand from the competition and improves customer retention. Let us know what your needs are to see if Private Label or OEM services is a better solution for you.

For more information contact us at:

sales@scpcat5e.com | Phone: +1 (954) 327-5770

SCP Corporate Office:

3490 SW 30th Ave, Dania Beach, FL 33312, USA

