

Speaker Cables Line Card (EU Warehouse)



Structured Cable Products ("SCP"), Fort Lauderdale, USA, is a leading manufacturer and global supplier of low voltage cables and connectivity accessories. SCP speaker cables provide the highest quality, performance and value on the market today. SCP offers a wide variety of speaker cable solutions to accommodate almost any installation need. Our speaker cables come in a variety of CPR jacket ratings, jacket colors, and packaging options. Most of our speaker cables come in our award winning "tangle free" boxes.

SCP **Structured Cable Products**
Quality Installations Deserve Quality Products

Manufacturer and Global Supplier



Commercial Speaker Cable Series - B2ca EuroClass

Rated for Use in Public and Commercial Buildings.

Features			Compliance		Applications		
High Strand Count Oxygen Free Copper; Unshielded; LSZH Insulated Twisted Pair; B2ca Rated LSZH Jacket; Easy Strip Jacket; Excellent Flexibility; Packaging - Reel-In-Box or Wooden Spool; Descending Meter and Zone/Outlet Jacket Markings.			EN50575 B2ca-s1a,d1,a1; IEC 60332-1-2; IEC 60754-1-2; IEC 61034-1,2; EN50399; RoHS		Commercial, Institutional, Residential; 100v Loudspeakers; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power; 4.0mm² Indoor/Outdoor Rated UV Sun Resistant.		
SCP Part Number	Cores	Conductor Size	Nom. OD	Jacket	Installation Rated	Packaged Length	Weight
SP-1.5/2-LSZH-BK-B2	2	1.5mm² (30*0.25)	5.8mm	LSZH - Black	B2ca-s1a,d1,a1	305m/1000ft Spool	16.9kgs/37lbs
SP-1.5/2-LSZH-WT	2	1.5mm² (30*0.25)	5.8mm	LSZH - White	B2ca-s1a,d1,a1	305m/1000ft Spool	16.9kgs/37lbs
SP-2.5/2-LSZH-BK-B2	2	2.5mm² (50*0.25)	6.8mm	LSZH - Black	B2ca-s1a,d1,a1	305m/1000ft Spool	24.5kgs/54lbs
SP-2.5/2-LSZH-BK-500	2	2.5mm² (50*0.25)	6.8mm	LSZH - Black	B2ca-s1a,d1,a1	152m/500ft Reel in Box	13.6kgs/30lbs
SP-2.5/2-LSZH-WT-500	2	2.5mm² (50*0.25)	6.8mm	LSZH - White	B2ca-s1a,d1,a1	152m/500ft Reel in Box	13.6kgs/30lbs
SP-2.5/4-LSZH-BK	4	2.5mm² (50*0.25)	8.0mm	LSZH - Black	B2ca-s1a,d1,a1	152m/500ft Reel in Box	23.2kgs/51lbs
SP-2.5/4-LSZH-WT	4	2.5mm² (50*0.25)	8.0mm	LSZH - White	B2ca-s1a,d1,a1	152m/500ft Reel in Box	23.2kgs/51lbs
SP-4.0/2-LSZH-BK-100M	2	4.0mm² (56*0.30)	8.5mm	UV LSZH - Black	B2ca-s1a,d1,a1	100m/328ft Reel in Box	13.6kgs/30lbs
SP-4.0/2-LSZH-WT-100M	2	4.0mm² (56*0.30)	8.5mm	UV LSZH - White	B2ca-s1a,d1,a1	100m/328ft Reel in Box	13.6kgs/30lbs
SP-4.0/2-LSZH-BK-500M	2	4.0mm² (56*0.30)	8.5mm	UV LSZH - Black	B2ca-s1a,d1,a1	500m/1640ft Spool	64.2kgs/142lbs
SP-4.0/4-LSZH-BK-100M	4	4.0mm² (56*0.30)	10.0mm	UV LSZH - Black	B2ca-s1a,d1,a1	100m/328ft Spool	23.8kgs/52lbs
SP-4.0/4-LSZH-BK-500M	4	4.0mm² (56*0.30)	10.0mm	UV LSZH - Black	B2ca-s1a,d1,a1	500m/1640ft Spool	112kgs/247lbs

Low Smoke Zero Halogen Commercial/Residential Series

High Strand Count Oxygen Free Copper Speaker Cable - Flexible Indoor Rated LSZH Jacket.

Features			Compliance		Applications		
Low Smoke Zero Halogen (LSZH) High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair; Easy Strip LSZH Jacket; SCP Tangle Free Reel/In Box; Descending Meter and SCP Zone/Outlet Jacket Markings.			EN50575 Dca-s1,d1,a1; IEC 60332-1-2; RoHS		Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power.		
SCP Part Number	Cores	Conductor Size	Nom. OD	Jacket	Installation Rated	Packaged Length	Weight
16/20FC-LSZH-BK-D	2	16AWG (65)	5.0mm	LSZH - Black	Dca-s1,d1,a1	152m/500ft Pull Box	6.8kgs/15lbs
16/20FC-LSZH-PUR-D	2	16AWG (65)	5.0mm	LSZH - Purple	Dca-s1,d1,a1	152m/500ft Pull Box	6.8kgs/15lbs
16/20FC-LSZH-WT	2	16AWG (65)	5.0mm	LSZH - White	Dca-s1,d1,a1	152m/500ft Pull Box	6.8kgs/15lbs
16/20FC-LSZH-BK-1000-D	2	16AWG (65)	5.0mm	LSZH - Black	Dca-s1,d1,a1	305m/1000ft Pull Box	13.6kgs/30lbs
16/20FC-LSZH-WT-1000	2	16AWG (65)	5.0mm	LSZH - White	Dca-s1,d1,a1	305m/1000ft Pull Box	13.6kgs/30lbs
H-16/20FC-LSZH-OR-1000	2	16AWG (65)	6.25mm	HD-LSZH - Orange	Dca-s1,d1,a1	305m/1000ft Pull Box	16.3kgs/36lbs
16/40FC-LSZH-BK-D	4	16AWG (65)	6.1mm	LSZH - Black	Dca-s1,d1,a1	152m/500ft Pull Box	11.8kgs/26lbs
16/40FC-LSZH-PUR-D	4	16AWG (65)	6.1mm	LSZH - Purple	Dca-s1,d1,a1	152m/500ft Pull Box	11.8kgs/26lbs
16/40FC-LSZH-WT	4	16AWG (65)	6.1mm	LSZH - White	Dca-s1,d1,a1	152m/500ft Pull Box	11.8kgs/26lbs
H-16/40FC-LSZH-OR	4	16AWG (65)	7.0mm	HD-LSZH - Orange	Dca-s1,d1,a1	152m/500ft Pull Box	13.5kgs/30lbs
14/20FC-LSZH-BK-D	2	14AWG (105)	6.3mm	LSZH - Black	Dca-s1,d1,a1	152m/500ft Pull Box	11.2kgs/25lbs
14/20FC-LSZH-PUR	2	14AWG (105)	6.3mm	LSZH - Purple	Dca-s1,d1,a1	152m/500ft Pull Box	11.2kgs/25lbs
14/20FC-LSZH-WT	2	14AWG (105)	6.3mm	LSZH - White	Dca-s1,d1,a1	152m/500ft Pull Box	11.2kgs/25lbs
14/40FC-LSZH-BK-D	4	14AWG (105)	8.0mm	LSZH - Black	Dca-s1,d1,a1	152m/500ft Reel in Box	22.5kgs/50lbs
14/40FC-LSZH-PUR	4	14AWG (105)	8.0mm	LSZH - Purple	Dca-s1,d1,a1	152m/500ft Reel in Box	22.5kgs/50lbs
14/40FC-LSZH-WT	4	14AWG (105)	8.0mm	LSZH - White	Dca-s1,d1,a1	152m/500ft Reel in Box	22.5kgs/50lbs
12/20FC-LSZH-BK-D	2	12AWG (65)	8.0mm	LSZH - Black	Dca-s1,d1,a1	152m/500ft Reel in Box	17kgs/37lbs
12/20FC-LSZH-WT	2	12AWG (65)	8.0mm	LSZH - White	Dca-s1,d1,a1	152m/500ft Reel in Box	17kgs/37lbs
12/40FC-LSZH-BK-D	4	12AWG (65)	9.4mm	LSZH - Black	Dca-s1,d1,a1	152m/500ft Spool	30kgs/66lbs
12/40FC-LSZH-WT-D	4	12AWG (65)	9.4mm	LSZH - White	Dca-s1,d1,a1	152m/500ft Spool	30kgs/66lbs

Pro Grade Indoor/Outdoor HD Series - Commercial and Residential

One Cable Solution for both In-Wall and Outdoor Installations Providing Superior Performance, Flexibility and Protection.

Features			Compliance		Applications		
High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair; CPR Rated Dca; HD UV Sun Resistant Jacket; Easy Strip Round Rope Lay Construction; SCP Tangle Free Reel II Box; Descending Meter and SCP Zone/Outlet Jacket Markings.			EN50575 Euroclass: Dca-s3,d2,a3; UL CMR CL2R/CL3R c(UL) FT4; RoHS; 300V, 75C; UL 444		Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power; UL Direct Burial; Outdoor: UV Sun Resistant; Indoor: In-Wall Riser Rated		
SCP Part Number	Cores	Conductor Size	Nom. OD	Jacket	Installation Rated	Packaged Length	Weight
16/20FC-HD-BK-D	2	16AWG (65)	6.25mm	UV HD-PVC - Black	Dca / UL CMR/CL3R	152m/500ft Pull Box	8.3kgs/18lbs
16/20FC-HD-PUR-D	2	16AWG (65)	6.25mm	UV HD-PVC - Purple	Dca / UL CMR/CL3R	152m/500ft Pull Box	8.3kgs/18lbs
16/20FC-HD-WT-D	2	16AWG (65)	6.25mm	UV HD-PVC - White	Dca / UL CMR/CL3R	152m/500ft Pull Box	8.3kgs/18lbs
H-16/20FC-OR-1000-D	2	16AWG (65)	6.25mm	HD-PVC - Orange	Dca / UL CMR/CL3R	305m/1000ft Pull Box	16.3kgs/36lbs
16/40FC-HD-BK-D	4	16AWG (65)	7.0mm	UV HD-PVC - Black	Dca / UL CMR/CL3R	152m/500ft Pull Box	11.8kgs/26lbs
16/40FC-HD-PUR-D	4	16AWG (65)	7.0mm	UV HD-PVC - White	Dca / UL CMR/CL3R	152m/500ft Pull Box	11.8kgs/26lbs
16/40FC-HD-WT-D	4	16AWG (65)	7.0mm	UV HD-PVC - White	Dca / UL CMR/CL3R	152m/500ft Pull Box	11.8kgs/26lbs
14/20FC-HD-BK-D	2	14AWG (105)	7.2mm	UV HD-PVC - Black	Dca / UL CL3R	152m/500ft Pull Box	12kgs/26.5lbs
14/20FC-HD-PUR-D	2	14AWG (105)	7.2mm	UV HD-PVC - Purple	Dca / UL CL3R	152m/500ft Pull Box	12kgs/26.5lbs
14/20FC-HD-WT-D	2	14AWG (105)	7.2mm	UV HD-PVC - White	Dca / UL CL3R	152m/500ft Pull Box	12kgs/26.5lbs
14/40FC-HD-BK-D	4	14AWG (105)	8.3mm	UV HD-PVC - Black	Dca / UL CL3R	152m/500ft Reel in Box	22.5kgs/50lbs
14/40FC-HD-WT-D	4	14AWG (105)	8.3mm	UV HD-PVC - White	Dca / UL CL3R	152m/500ft Reel in Box	22.5kgs/50lbs
12/20FC-HD-BK-D	2	12AWG (65)	8.3mm	UV HD-PVC - Black	Dca / UL CL3R	152m/500ft Reel in Box	17kgs/37.5lbs
12/20FC-HD-WT-D	2	12AWG (65)	8.3mm	UV HD-PVC - White	Dca / UL CL3R	152m/500ft Reel in Box	17kgs/37.5lbs
12/40FC-HD-WT-D	4	12AWG (65)	9.8mm	UV HD-PVC - White	Dca / UL CL3R	152m/500ft Spool	30kgs/66lbs

In-Wall Residential Series

High Strand Count Oxygen Free Copper Speaker Cable with Smaller Cable OD for Easy Installation When Bundling through Conduit.

Features			Compliance		Applications		
High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair; Smaller Cable OD; Flexible Easy Strip PVC Jacket; SCP Tangle Free Reel II Box Packaging; Descending Meter and SCP Zone/Outlet Jacket Markings.			EN50575 Euroclass: Dca-s3,d2,a3; UL CMR CL2R/CL3R c(UL) FT4; RoHS; 300V, 75C; UL 444		Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Ideal for Conduit/Tube Installs; Class 2/3 Low Voltage Power; Indoor: In-Wall Riser Rated.		
SCP Part Number	Cores	Conductor Size	Nom. OD	Jacket	Installation Rated	Packaged Length	Weight
16/20FC-WT-D	2	16AWG (65)	5.0mm	PVC - White	Dca / UL CMR/CL3R	152m/500ft Pull Box	6.7kgs/15lbs
16/40FC-WT-D	4	16AWG (65)	6.1mm	PVC - White	Dca / UL CMR/CL3R	152m/500ft Pull Box	11.8kgs/26lbs
14/20FC-WT-D	2	14AWG (105)	6.3mm	PVC - White	Dca / UL CL3R	152m/500ft Pull Box	11kgs/24lbs
14/40FC-WT-D	4	14AWG (105)	8.0mm	PVC - White	Dca / UL CL3R	152m/500ft Pull Box	22kgs/49lbs

Contractor Economical Series

High Strand Count Oxygen Free Copper Speaker Cable with Smaller Cable OD for Easy Installation When Bundling through Conduit.

Features			Compliance		Applications		
Oxygen Free Copper; Unshielded; Insulated twisted pair; Easy Strip PVC Jacket; SCP Tangle Free Reel II Box; Descending Meter and SCP Zone/Outlet Jacket Markings.			EN50575 Euroclass: Eca; UL CMR CL2R/CL3R c(UL) FT4; RoHS; 300V, 75C; UL 444		Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power.		
SCP Part Number	Cores	Conductor Size	Nom. OD	Jacket	Installation Rated	Packaged Length	Weight
16/25P-26-WT	2	16AWG (26)	5.0mm	PVC - White	Eca / UL CMR/CL3R	152m/500ft Pull Box	6.7kgs/15lbs
16/45P-26-WT	4	16AWG (26)	6.1mm	PVC - White	Eca / UL CMR/CL3R	152m/500ft Pull Box	6.7kgs/15lbs

Landscape / Direct Burial Professional Series

Professionals Choice for All High Performance Landscape and Outdoor Speaker Systems. Retains Flexibility in All Outdoor Environments. Recommended by Leading Speaker Brands.

Features			Compliance		Applications		
High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair; LLDPE Jacket; Waterproof; Gel Filled; Superior Durability and Longevity; Rodent Resistant; UV Sun Resistant; Descending Meter Markings.			UL 444, NEC CL3, RoHS		Professional Outdoor Speaker Systems; Direct Burial Waterproof; Audio/Security/Control; Class 2/3 Low Voltage Power; Installs in Wet Environments; Commercial/Residential/Institutional.		
SCP Part Number	Cores	Conductor Size	Nom. OD	Jacket	Installation Rated	Packaged Length	Weight
14/25P-DB-100	2	14AWG (105)	6.4mm	LLDPE - Black	Direct Burial/Outdoor	100m/328ft Spool	7.7kgs/17lbs
14/25P-DB-500	2	14AWG (105)	6.4mm	LLDPE - Black	Direct Burial/Outdoor	152m/500ft Spool	11.7kgs/26lbs
14/45P-DB-100	4	14AWG (105)	8.2mm	LLDPE - Black	Direct Burial/Outdoor	100m/328ft Spool	14kgs/31lbs
14/45P-DB-GEL-500	4	14AWG (105)	8.2mm	LLDPE - Black	Direct Burial/Outdoor	152m/500ft Spool	21kgs/46lbs

All weights and dimensions are approximate and every effort has been made to ensure its accuracy at time of publication. The information herein is subject to change without notice.



Private Label & OEM Services

SCP is a manufacturer and product developer. SCP is an industry leader in cable and connectivity development. Are you interested in private label or OEM services for bulk cables or connectivity solutions? Private Label can differentiate your brand from the competition and improves customer retention. Let us know what your needs are to see if Private Label or OEM services is a better solution for you.

For more information contact us at:
sales@scpcat5e.com | Phone: +1 (954) 327-5770

SCP EU Warehouse:
 DSV - Marconiweg 3, Tholen 4691 SV, Netherlands

