

Speaker Cables Line Card (USA Warehouses)



Structured Cable Products ("SCP") is a leading manufacturer and global supplier of low voltage cables and connectivity accessories. SCP speaker cables provide the highest quality, performance and value on the market today. SCP offers a wide variety of speaker cable solutions to accommodate almost any installation need. Our speaker cables are UL Listed and come in a variety of jacket colors, and packaging options. Most of our speaker cables come in our award winning "tangle free" boxes.

SCP Structured Cable Products®
Quality Installations Deserve Quality Products

Manufacturer and Global Supplier



Pro Grade Indoor/Outdoor HD Series - Commercial and Residential

One Cable Solution for both In-Wall and Outdoor Installations Providing Superior Performance, Flexibility and Protection.

Features			Compliance		Applications		
Highly Flexible. Indoor/Outdoor Rated. High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair BK/RD & BK/RD/GN/WT; HD UV Sun Res PVC Jacket; Easy Strip Round Rope Lay Construction; SCP Tangle Free Reel II Box; Descending Feet and Zone/Outlet Jacket Markings			UL CMR CL2R/CL3R c(UL) FT4; RoHS; Low Voltage & Power Limited Systems; 300V 75°C; 14-12AWG are not recognized by c(UL).		Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power; UL Direct Burial; Outdoor: UV Sun Resistant ; Indoor: In-Wall Riser Rated		
SCP Part Number	AWG	Conductors	Nom. OD	Jacket / Color	Installation Rated	Packaging	Weight
16/20FC-HD-BK	16	2/65 Str OFC	6.25mm/0.246"	HD UV-PVC - Black	UL CMR/CL3R	152m/500ft Pull Box	8.3kgs/18lbs
16/20FC-HD-PUR	16	2/65 Str OFC	6.25mm/0.246"	HD UV-PVC - Purple	UL CMR/CL3R	152m/500ft Pull Box	8.3kgs/18lbs
16/20FC-HD-WT	16	2/65 Str OFC	6.25mm/0.246"	HD UV-PVC - White	UL CMR/CL3R	152m/500ft Pull Box	8.3kgs/18lbs
16/40FC-HD-BK	16	4/65 Str OFC	7.0mm/0.275"	HD UV-PVC - Black	UL CMR/CL3R	152m/500ft Pull Box	12kgs/26lbs
16/40FC-HD-PUR	16	4/65 Str OFC	7.0mm/0.275"	HD UV-PVC - Purple	UL CMR/CL3R	152m/500ft Pull Box	12kgs/26lbs
16/40FC-HD-WT	16	4/65 Str OFC	7.0mm/0.275"	HD UV-PVC - White	UL CMR/CL3R	152m/500ft Pull Box	12kgs/26lbs
14/20FC-HD-BK	14	2/105 Str OFC	7.2mm/0.283"	HD UV-PVC - Black	UL CL3R	152m/500ft Pull Box	12kgs/26lbs
14/20FC-HD-PUR	14	2/105 Str OFC	7.2mm/0.283"	HD UV-PVC - Purple	UL CL3R	152m/500ft Pull Box	12kgs/26lbs
14/20FC-HD-WT	14	2/105 Str OFC	7.2mm/0.283"	HD UV-PVC - White	UL CL3R	152m/500ft Pull Box	12kgs/26lbs
14/40FC-HD-BK	14	4/105 Str OFC	8.3mm/0.326"	HD UV-PVC - Black	UL CL3R	152m/500ft Reel in Box	22.5kgs/50lbs
14/40FC-HD-PUR	14	4/105 Str OFC	8.3mm/0.326"	HD UV-PVC - Purple	UL CL3R	152m/500ft Reel in Box	22.5kgs/50lbs
14/40FC-HD-WT	14	4/105 Str OFC	8.3mm/0.326"	HD UV-PVC - White	UL CL3R	152m/500ft Reel in Box	22.5kgs/50lbs
12/20FC-HD-BK	12	2/65 Str OFC	8.3mm/0.326"	HD UV-PVC - Black	UL CL3R	152m/500ft Reel in Box	17kgs/37lbs
12/20FC-HD-WT	12	2/65 Str OFC	8.3mm/0.326"	HD UV-PVC - White	UL CL3R	152m/500ft Reel in Box	17kgs/37lbs
12/40FC-HD-WT	12	4/65 Str OFC	9.8mm/0.385"	HD UV-PVC - White	UL CL3R	152m/500ft Spool	30kgs/66lbs

In-Wall Series

High Strand Count Oxygen Free Copper Speaker Cable with Smaller Cable OD for Easy Installation When Bundling through Conduit.

Features			Compliance		Applications		
Highly Flexible. High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair BK/RD & BK/RD/GN/WT; Easy Strip PVC Jkt; Smaller OD ideal for conduit. SCP Tangle Free Reel II Box; Descending Feet and Zone/Outlet Jacket Markings			UL CMR CL2R/CL3R c(UL) FT4; RoHS; Low Voltage & Power Limited Systems; 300V 75°C; 14-12AWG are not recognized by c(UL).		Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power; In-Wall Riser Rated		
SCP Part Number	AWG	Conductors	Nom. OD	Jacket / Color	Installation Rated	Packaging	Weight
16/20FC-BK	16	2/65 Str OFC	5.0mm/0.196"	PVC - Black	UL CMR/CL3R	500ft Pull Box	6.7kgs/15lbs
16/20FC-PUR	16	2/65 Str OFC	5.0mm/0.196"	PVC - Purple	UL CMR/CL3R	500ft Pull Box	6.7kgs/15lbs
16/20FC-PUR-1000	16	2/65 Str OFC	5.0mm/0.196"	PVC - Purple	UL CMR/CL3R	1000ft Pull Box	13.6kgs/30lbs
16/20FC-WT	16	2/65 Str OFC	5.0mm/0.196"	PVC - White	UL CMR/CL3R	500ft Pull Box	6.7kgs/15lbs
16/20FC-WT-1000	16	2/65 Str OFC	5.0mm/0.196"	PVC - White	UL CMR/CL3R	1000ft Pull Box	13.6kgs/30lbs
16/20FC-WT-HDBX	16	2/65 Str OFC	5.0mm/0.196"	PVC - White	UL CMR/CL3R	500ft Heavy Duty Box	8.3kgs/18lbs
16/40FC-BK	16	4/65 Str OFC	6.1mm/0.24"	PVC - White	UL CMR/CL3R	500ft Pull Box	11.8kgs/26lbs
16/40FC-OR	16	4/65 Str OFC	6.1mm/0.24"	PVC - White	UL CMR/CL3R	500ft Pull Box	11.8kgs/26lbs
16/40FC-PUR	16	4/65 Str OFC	6.1mm/0.24"	PVC - Purple	UL CMR/CL3R	500ft Pull Box	11.8kgs/26lbs
16/40FC-WT	16	4/65 Str OFC	6.1mm/0.24"	PVC - White	UL CMR/CL3R	500ft Pull Box	11.8kgs/26lbs
14/20FC-BK	14	2/105 Str OFC	6.3mm/0.248"	PVC - Black	UL CL3R	500ft Pull Box	11kgs/24lbs
14/20FC-PUR	14	2/105 Str OFC	6.3mm/0.248"	PVC - Purple	UL CL3R	500ft Pull Box	11kgs/24lbs
14/20FC-WT	14	2/105 Str OFC	6.3mm/0.248"	PVC - White	UL CL3R	500ft Pull Box	11kgs/24lbs
14/40FC-BK	14	4/105 Str OFC	8.0mm/0.314"	PVC - Black	UL CL3R	500ft Reel-In-Box	22kgs/49lbs
14/40FC-PUR	14	4/105 Str OFC	8.0mm/0.314"	PVC - Purple	UL CL3R	500ft Reel-In-Box	22kgs/49lbs
14/40FC-WT	14	4/105 Str OFC	8.0mm/0.314"	PVC - White	UL CL3R	500ft Reel-In-Box	22kgs/49lbs
12/20FC-WT	12	2/65 Str OFC	8.0mm/0.314"	PVC - White	UL CL3R	500ft Reel-In-Box	16.2kgs/36lbs
12/40FC-WT	12	4/65 Str OFC	9.4mm/0.37"	PVC - White	UL CL3R	500ft Spool	28.7kgs/63lbs

Low Smoke Zero Halogen Commercial/Residential Series

High Strand Count Oxygen Free Copper Speaker Cable - Flexible Indoor Rated LSZH Jacket.

Features			Compliance		Applications		
High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair; Easy Strip LSZH Jacket; SCP Tangle Free Reel/II Box; Descending Feet and SCP Zone/Outlet Jacket Markings			Low Smoke Zero Halogen, IEC 60332-1-2; Low Voltage & Power Limited Systems; 300V 75°C; RoHS		Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power; Marine		
SCP Part Number	AWG	Conductors	Nom. OD	Jacket / Color	Installation Rated	Packaging	Weight
16/20FC-LSZH-WT	16	2/65 Str OFC	5.0mm/0.196"	LSZH - White	In-Wall & Marine	152m/500ft Pull Box	6.8kgs/15lbs
14/20FC-LSZH-PUR	14	2/105 Str OFC	6.3mm/0.248"	LSZH - Purple	In-Wall & Marine	152m/500ft Pull Box	11.2kgs/25lbs
14/20FC-LSZH-WT	14	2/105 Str OFC	6.3mm/0.248"	LSZH - White	In-Wall & Marine	152m/500ft Pull Box	11.2kgs/25lbs

Contractor Series

Contractor Grade Speaker Cables for Standard Installations

Features			Compliance		Applications		
Oxygen Free Copper; Unshielded; Insulated twisted pair; Easy Strip PVC Jacket; SCP Tangle Free Reel/II Box; Descending Meter and SCP Zone/Outlet Jacket Markings			UL CMR CL2R/3R c(UL) FT4; RoHS; Low Voltage & Power Limited Systems; 300V 75°C		Residential; Speaker, Audio, Control; In-Wall Speakers; Class 2/3 Low Voltage Power		
SCP Part Number	AWG	Conductors	Nom. OD	Jacket / Color	Installation Rated	Packaging	Weight
16/2SP-26-BL	16	2/26 Str OFC	5.0mm/0.196"	PVC - Blue	UL CMR/CL3R	500ft Pull Box	6.7kgs/15lbs
16/2SP-26-GN	16	2/26 Str OFC	5.0mm/0.196"	PVC - Green	UL CMR/CL3R	500ft Pull Box	6.7kgs/15lbs
16/2SP-26-WT	16	2/26 Str OFC	5.0mm/0.196"	PVC - White	UL CMR/CL3R	500ft Pull Box	6.7kgs/15lbs
16/2SP-26-WT-1000	16	2/26 Str OFC	5.0mm/0.196"	PVC - White	UL CMR/CL3R	1000ft Pull Box	13.6kgs/30lbs
16/2SP-65-PUR-1000	16	2/65 Str OFC	5.0mm/0.196"	PVC - Purple	UL CMR/CL3R	1000ft Pull Box	13.6kgs/30lbs
16/4SP-26-BL	16	4/26 Str OFC	6.1mm/0.24"	PVC - Blue	UL CMR/CL3R	500ft Pull Box	11.8kgs/26lbs
16/4SP-26-WT	16	4/26 Str OFC	6.1mm/0.24"	PVC - White	UL CL3R	500ft Pull Box	11.8kgs/26lbs
14/2SP-41-YL	14	2/41 Str OFC	6.4mm/0.252"	PVC - Yellow	UL CL3R	500ft Pull Box	11kgs/24lbs
14/2SP-41-YL-1000	14	2/41 Str OFC	6.4mm/0.252"	PVC - Yellow	UL CL3R	1000ft Spool	21.8kgs/48lbs
14/4SP-41-YL	14	4/41 Str OFC	8.0mm/0.314"	PVC - Yellow	UL CL3R	500ft Reel in Box	19.9kgs/44lbs

Landscape / Direct Burial Professional Series

Professionals Choice for All High Performance Landscape and Outdoor Speaker Systems. Retains Flexibility in All Outdoor Environments. SCP Cat5e Direct Burial cables feature LLDPE (Linear Low-Density Polyethylene) jackets that provide superior performance and durability over PVC or standard PE jacket cables. These cables also are UV Sun Resistant and retains flexible performance in both hot and cold environments. Recommended by Leading Speaker Brands.

Features			Compliance		Applications		
High Strand Count Oxygen Free Copper; Unshielded; Insulated twisted pair; Easy Strip LSZH Jacket; SCP Tangle Free Reel/II Box; Descending Feet and SCP Zone/Outlet Jacket Markings			Low Smoke Zero Halogen, IEC 60332-1-2; Low Voltage & Power Limited Systems; 300V 75°C; RoHS		Commercial & Residential; High Definition; Home Theater Systems, In-Wall Speakers; Class 2/3 Low Voltage Power; Marine		
SCP Part Number	AWG	Conductors	Nom. OD	Jacket / Color	Installation Rated	Packaging	Weight
14/2SP-DB-500	14	2/105 Str OFC	6.4mm/0.252"	LLDPE - Black	Direct Burial/Outdoor	152m/500ft Spool	11.7kgs/26lbs
14/4SP-DB-GEL	14	4/105 Str OFC	8.2mm/0.323"	LLDPE - Black	Direct Burial/Outdoor	305m/1000ft Spool	40kgs/88lbs
14/4SP-DB-GEL-500	14	4/105 Str OFC	8.2mm/0.323"	LLDPE - Black	Direct Burial/Outdoor	152m/500ft Spool	21kgs/46lbs

All weights and dimensions are approximate and every effort has been made to ensure its accuracy at time of publication. The information herein is subject to change without notice.



Private Label & OEM Services

SCP is a manufacturer and product developer. SCP is an industry leader in cable and connectivity development. Are you interested in private label or OEM services for bulk cables or connectivity solutions? Private Label can differentiate your brand from the competition and improves customer retention. Let us know what your needs are to see if Private Label or OEM services is a better solution for you.

For more information contact us at:
sales@scpcat5e.com | Phone: +1 (954) 327-5770

SCP Corporate Office:
 3490 SW 30th Ave, Dania Beach, FL 33312, USA

