



# Structured Cable Products

Quality Installations Deserve Quality Products

## HNC-5 - HOME NETWORKING CABLE

PART# HNC-5

75 ohm 2xRG-6/U Quad Shield + 1xCAT5E Triamese Cable																																																																	
RoHS compliance																																																																	
Part / Model Number : HNC-5-500-GY / AL-HNC-5																																																																	
CROSS SECTION	PROPERTIES																																																																
	<b>Min.Bending Radius:</b> Loaded 20 Times Cable OD Unloaded 10 Times Cable OD <b>Max.Pulling Tension</b> 126 LBS <b>Rated Temperature (°C)</b> -20~+75																																																																
CONSTRUCTION	ELETRICAL CHARACTERISTICS																																																																
<table border="0"> <tr> <td></td> <td><b>A</b></td> <td><b>B &amp; C</b></td> </tr> <tr> <td><b>Conductor</b></td> <td>B. Copper</td> <td>B. Copper</td> </tr> <tr> <td>Diameter (+/-0.02mm)</td> <td>0.510</td> <td>1.020</td> </tr> <tr> <td><b>Insulation</b></td> <td></td> <td>FPE</td> </tr> <tr> <td>Diameter (+/-0.10 mm)</td> <td>0.91</td> <td>4.57</td> </tr> <tr> <td><b>First Shielding (mm)</b></td> <td></td> <td>AL/P-Foil(Bonded) 17x0.022mm</td> </tr> <tr> <td><b>First Braiding</b></td> <td></td> <td>AL Wire Braid</td> </tr> <tr> <td>Construction (+/- 0.01 mm)</td> <td></td> <td>0.16mm x64</td> </tr> <tr> <td>Coverage</td> <td></td> <td>60%</td> </tr> <tr> <td>Picks/dm</td> <td></td> <td>20</td> </tr> <tr> <td>Lay length (mm)</td> <td></td> <td>40</td> </tr> <tr> <td><b>Second Shielding (mm)</b></td> <td></td> <td>AL/P/AL-Foil 31x0.029mm</td> </tr> <tr> <td><b>Second Braiding</b></td> <td></td> <td>AL Wire Braid</td> </tr> <tr> <td>Construction (+/- 0.01 mm)</td> <td></td> <td>0.16mm x48</td> </tr> <tr> <td>Coverage</td> <td></td> <td>40%</td> </tr> <tr> <td>Picks/dm</td> <td></td> <td>20</td> </tr> <tr> <td>Lay length (mm)</td> <td></td> <td>40</td> </tr> <tr> <td><b>Jacket</b></td> <td>PVC x 1</td> <td>PVC x 2</td> </tr> <tr> <td>Outer Dia (+/-0.1mm)</td> <td>5.50</td> <td>7.62+7.62</td> </tr> <tr> <td>Color</td> <td>Grey</td> <td>Grey</td> </tr> <tr> <td><b>Length</b></td> <td colspan="2">500 Ft / Plywood Drum or as per Contract</td> </tr> </table>		<b>A</b>	<b>B &amp; C</b>	<b>Conductor</b>	B. Copper	B. Copper	Diameter (+/-0.02mm)	0.510	1.020	<b>Insulation</b>		FPE	Diameter (+/-0.10 mm)	0.91	4.57	<b>First Shielding (mm)</b>		AL/P-Foil(Bonded) 17x0.022mm	<b>First Braiding</b>		AL Wire Braid	Construction (+/- 0.01 mm)		0.16mm x64	Coverage		60%	Picks/dm		20	Lay length (mm)		40	<b>Second Shielding (mm)</b>		AL/P/AL-Foil 31x0.029mm	<b>Second Braiding</b>		AL Wire Braid	Construction (+/- 0.01 mm)		0.16mm x48	Coverage		40%	Picks/dm		20	Lay length (mm)		40	<b>Jacket</b>	PVC x 1	PVC x 2	Outer Dia (+/-0.1mm)	5.50	7.62+7.62	Color	Grey	Grey	<b>Length</b>	500 Ft / Plywood Drum or as per Contract		<b>Characteristic Impedance</b> 75 +/- 3 ohm <b>Capacitance</b> 52 pF/m <b>Velocity Ratio</b> 81% <b>DCR : Conductor</b> < 21 ohm / km <b>DCR : Shielding</b> < 19 ohm / km <b>Sparker</b> 4000 VCA <b>Dielectric Strength</b> 2500 VCA <b>Return loss</b> 5 - 470MHz 23 dB 470 - 1000MHz 20 dB 1000 - 2200MHz 20 dB	
	<b>A</b>	<b>B &amp; C</b>																																																															
<b>Conductor</b>	B. Copper	B. Copper																																																															
Diameter (+/-0.02mm)	0.510	1.020																																																															
<b>Insulation</b>		FPE																																																															
Diameter (+/-0.10 mm)	0.91	4.57																																																															
<b>First Shielding (mm)</b>		AL/P-Foil(Bonded) 17x0.022mm																																																															
<b>First Braiding</b>		AL Wire Braid																																																															
Construction (+/- 0.01 mm)		0.16mm x64																																																															
Coverage		60%																																																															
Picks/dm		20																																																															
Lay length (mm)		40																																																															
<b>Second Shielding (mm)</b>		AL/P/AL-Foil 31x0.029mm																																																															
<b>Second Braiding</b>		AL Wire Braid																																																															
Construction (+/- 0.01 mm)		0.16mm x48																																																															
Coverage		40%																																																															
Picks/dm		20																																																															
Lay length (mm)		40																																																															
<b>Jacket</b>	PVC x 1	PVC x 2																																																															
Outer Dia (+/-0.1mm)	5.50	7.62+7.62																																																															
Color	Grey	Grey																																																															
<b>Length</b>	500 Ft / Plywood Drum or as per Contract																																																																
	<b>Attenuation at 20 C (dB/100m) for RG-6/U Quad</b> 1.00 0.67 3.60 1.19 10.00 1.99 71.50 5.42 135.00 7.53 270.00 10.83 360.00 12.61 720.00 18.31 1000.00 21.92 1500.00 27.46 2000.00 32.31 2250.00 36.71 3000.00 40.80																																																																
	<b>Cable Description</b> 1x CAT5E 24 AWG UTP + 2x RG6/U QUAD SHIELD COAX BC - (TRIAMESE)- 500 FT SPOOL- GRAY <b>Reference Standard</b> SCTE IPS-SP-001, UL1655, UL13, UL444 UL : CMX, CMG, CM, CMR																																																																
One CAT 5E UTP Solid 350MHz LAN Cable 24AWG 4Pairs Complies to TIA/EIA-568-B.2 & IEC / ISO 11801 24AWG Solid Bare Copper Conductor/PE Insulation Please see attachment-1 / Page 2 of 2 for details  <b>All specifications are subjected to change without prior notice.</b>																																																																	