

SCP PART#: LUT-GREEN-D-BX

Description:

Dca EUROCLASS- CONTROL/KEYPAD- 2C/22 AWG SHIELDED + 2C/18 AWG STRANDED + DRAIN, UL CM, EN50575 Dca-s3,d2,a3 PVC JKT (Compare to Lutron GRX-CBL-346S) - BLUE W/GREEN STRIPE- 305M/1000FT BOX


*Lutron®, Homeworks®, Sivoia®, Grafik Eye®, and Quantum Systems® are registered trademarks of Lutron Electronics Co., Inc Structured Cable Products Inc. is not affiliated with Lutron and our products are not endorsed or certified by Lutron.

Standard:

UL 444 & UL 13, Type (UL) CM,CMG/CL2 c(UL)
EU RoHS 2011/65/EU Compliant
EN50575
REACTION TO FIRE CPR Euroclass Dca-s3,d2,a3

Construction Characteristics:

Conductor A	Material	Stranded Bare Copper
	Size	18AWG X 2C
	Construction	16/0.254+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.24mm
	AVG.Thickness	0.26mm
	Diameter	1.70+/-0.05mm
Colors	Black & Red	
	Conductor 1P	Material
Size	22AWG X 2C	
	Construction	7/0.254+/-0.004mm
Insulation	Material	FPE
	Min.Thickness	0.56mm
	AVG.Thickness	0.60mm
	Diameter	2.00+/-0.05mm
	Colors	Purple & White
Shield	Drain wire(TC)	7/0.20+/-0.004mm
	Shield	AL Foil
Assembly(2C+1P)	Core wrap	PE Tape
Jacket	Material	Flame rated PVC
	Min.Thickness	0.67mm
	AVG.Thickness	0.75mm
	Diameter	6.35+/-0.20mm
	Rip Cord	Nylon
Color	Blue with Green Stripe	
Bend Radius	Min 20D/130mm	



Electrical & Physical Characteristics:

Operating Temperature Range		- 20°C + 70°C	
Conductor Resistance(18AWG)		Max 22.8ohm/km at 20°C	
Conductor Resistance(22AWG)		Max 53.5ohm/km at 20°C	
18AWG Core/Core Capacitance		130+/-30pf/m	
22AWG Core/Core Capacitance		40+/-15pf/m	
22AWG Core/Screen Capacitance		100+/-30pf/m	
Rated Voltage		Max 300Volts	
Dielectric Strength		Min AC1.5KV	
Insulation PVC	Unaged	Tensile Strenght	13.8Mpa
	Aged	Elongation	100%
		Tensile Strenght	11.7Mpa(100°C 168h)
Jacket	Unaged	Elongation	50%(100°C 168h)
		Tensile Strenght	13.8Mpa
	Aged	Elongation	100%
		Tensile Strenght	11.7Mpa(100°C 168h)
		Elongation	50%(100°C 168h)

Marking:

STRUCTURED CABLE PRODUCTS --- LUT-GREEN-D --- E198137 SCP3 (UL) CL2 C(UL) CM 2C/22AWG STR SHIELDED + 2C/18AWG STR EN50575:2014 CE Dca-s3,d2,a3 PVC JKT RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***M

Packaging:

Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
17.7kgs/39.02lbs	405*258*418	1000ft/305m Box	30/20