



# SPECIFICATION SHEET

14-May-2014

**Product Number : 14/2FPLR-YL**

**RoHS**

**Description : 2C/14 AWG SOLID FPLR PVC- YELLOW- 1000 FT SPOOL**

Conductor : 14 AWG Solid SBC Conductor	
Total Cable Weight : 55 kg/km	Final Diameter : 0.198 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 2.6 Ohms / 1000 ft	Mutual Capacitance : 22.9 pF/ft
Impedance : 70.2 Ohms	
Velocity of Prop : 72 %	Inductance. : 1.2 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 14/2FPLR - - - RISER FIRE ALARM CABLE (UL) CL2R/CL3R E198137 OR FPLR UNSH 2/C 14 AWG SOLID PVC JKT --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.137	NEC Articles : 760 FPLR
Ins Thickness: 0.010	Min. Bend Radius/Minor Axis : 1.386 inches
Jkt Thickness: 0.015	Operating Temperature : -20°C to 60°C
Certified: UL CL2R/CL3R or FPLR	Standard UL Temp : 60°C
Flame Rating: Riser	
Max Voltage: 300V	

Package Weight: 35 lbs / 15.91 kgs

( All of the above values are approximated to within +/- 10% )

2981402.03S.1000