

SCP PART#: 14/4-GY

DESCRIPTION : 4C/14 AWG 19-Strand BC, Unshielded MultiPurpose, UL CMR PVC 01/21
Gray- 1000 FT Spool

Unsh Riser 4/C 14/19 AWG SBC
PVC Insulation
Gray PVC Riser Jacket
1000 FEET Plywood Spool

Conductor : 14 AWG 19 Strand SBC Cond.	
Total Cable Weight : 105 kg/km	Final Diameter : 0.267 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 2.7 Ohms / 1000 ft	Mutual Capacitance : 22.3 pF/ft
Impedance : 74.8 Ohms	
Velocity of Prop : 70 %	Inductance. : 1.2 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)
 Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 14/4 - - - (UL) CL3R E198137 (UL)
 C(UL) CMR UNSH 4/C 14 AWG AUDIO ONLY - - - ZONE/DEVICE A B C D E 0
 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.134
 Ins Thickness: 0.010
 Jkt Thickness: 0.015
 Certified: UL CMR/CL3R
 Flame Rating: Riser
 Max Voltage: 300V

(All of the above values are approximated to within +/- 10%)