



Structured Cable Products™


Quality Installations Deserve Quality Products

www.spcat5e.com
 sales@scpat5e.com
 Direct: 954-327-5770
 Toll Free: 866-470-5742

SCP PART#: 16/2DB UPC: 817777012743

DESCRIPTION:

2C/ 16 AWG 65 STRAND DIRECT BURIAL W/WATER BLOCK TAPE- 1000 FT SPOOL- BLACK



Standard:

EU RoHS 2011/65/EU Compliant

Construction Characteristics:

Conductor	Material	Stranded Bare Copper
	Size	16AWG X 2C(1.31mm ²)
	Construction	65/0.16+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.30mm
	AVG.Thickness	0.33mm
	Diameter	2.0+/-0.05mm
Screen	Core wrap	PE Tape
	Filler	Water proof
Jacket	Material	LLDPE
	Min.Thickness	0.60mm
	AVG.Thickness	0.70mm
	Diameter	5.5+/-0.20mm
	Rip Cord	Nylon
	Color	Black
Bend radius	Min 15D/85mm	

Electrical & Physical Characteristics:

Operating Temperature Range	- 20°C + 75°C
Installation Temperature Range	0°C + 40°C
Conductor Resistance(16AWG)	Max 15.5ohm/km at 20°C
Insulation Resistance	Min 50MΩ*km at 20°C
Dielectric Strength	Min AC1.5KV
Rated Voltage	Max 80Volts
Impedance(near by):	85 ± 5 Ω
Capacitance(near by):	23 ± 3pf/ft

Marking:

STRUCTURED CABLE PRODUCTS --- 16/2DB -- 2C 16AWG 65 STRAND OFC DIRECT BURIAL WATER BLOCK TAPE - LLDPE JKT - EU RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***M

Packaging:

Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
14.6kgs/32.186lbs	360x220x160	1000ft/Spool	36