



Toll Free: 866-470-5742  
 Direct Line: 954-327-5770  
[www.scp5e.com](http://www.scp5e.com)  
[Sales@scp5e.com](mailto:Sales@scp5e.com)

## SPECIFICATION SHEET

**Product Number : 18/4P**

**RoHS**

**Description : 4C/18 AWG STRANDED PLENUM- WHITE- 1000 FT SPOOL**

Conductor :	18 AWG 7 Strand SBC Cond.		
Total Cable Weight :	45 kg/km	Final Diameter :	0.184 inches
Insulation :	PVC	Jacket :	PVC
DC Resistance 25°C:	6.7 Ohms / 1000 ft	Mutual Capacitance :	27.9 pF /ft
Impedance :	64.7 Ohms		
Velocity of Prop :	62 %	Inductance . :	1.4 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 18/4P --- (UL) CL2P/CL3P  
 E132885 OR FPLP 75°C (UL) C(UL) CMP FT-6 UNSH 4/C 18 AWG ---  
 ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.138	NEC Articles: 800, 760, 725
Ins Thickness: 0.008	Min. Bend Radius/Minor Axis: 1.288 inches
Jkt Thickness: 0.015	Operating Temperature : -20°C to 75°C
Certified: UL CL2P/CL3P OR FPLP/CMP	Standard UL Temp : 75°C
Flame Rating: FT-6	
Max Voltage: 300V	

Package Weight: 40 lbs / 18.18 kgs

( All of the above values are approximated to within +/- 10% )