

SCP PART#: 22/2P

01/21

Description : 2C/22 AWG STRANDED PLENUM- WHITE- 1000 FT SPOOL

Conductor : 22 AWG 7x.0097 Bare Copper	
Total Cable Weight : 13 kg/km	Final Diameter : 0.120 inches / 3.05mm
Insulation : Plenum	Jacket : Plenum
DC Resistance 25°C: 17.8 Ohms / 1000 ft	Mutual Capacitance : 17.9 pF/ft
Impedance : 82 Ohms	
Velocity of Prop : 65 %	Inductance. : 1.5 mH/km
Print Notes :	Sequentially marked per 2FT (0 - infinity)
Standard Print :	STRUCTURED CABLE PRODUCTS --- P/N 22/2P --- (UL) CL2P/CL3P E132885 OR FPLP 75°C (UL) C(UL) CMP FT-6 UNSH 2/C 22 AWG --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS
Cabled OD Avg: 0.074	NEC Articles: 800, 760, 725
Ins Thickness: 0.008	Min. Bend Radius/Minor Axis: .84 inches
Jkt Thickness: 0.015	Operating Temperature : -20°C to 75°C
Certified: UL CL2P/CL3P OR FPLP/CMP	Standard UL Temp : 75°C
Flame Rating: Plenum	
Max Voltage: 300V	

Package Weight: 10 lbs / 4.55 kgs

(All of the above values are approximated to within +/- 10%)