



Structured Cable Products™

Quality Installations Deserve Quality Products

www.scpcat5e.com
 sales@scpcat5e.com
 Direct: 954-327-5770
 Toll Free: 866-470-5742

SCP PART#: 22/2SH-GY

UPC: 810070012007

DESCRIPTION:

Shielded Riser 1/PR 22/7 AWG SBC, PVC Insulation, Gray PVC Riser Jacket, 1000 FEET/305M

General Specification of Product :

Final Diameter :	0.116 inches	2.946 mm
Total Cable Weight:	16 kg/km	11 lbs/1000 ft
Conductor :	22 AWG 7x.0097 Bare Copper	
Insulation :	PVC	
Shield :	Foil Shield 0.5	
Drain \ Ground:	24 AWG 7 Strand STC Cond.	
Outer Jacket :	PVC	

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/2SH - - - (UL) CL3R
 E198137-SCP (UL) C(UL) CMR SHIELDED 1/PR 22 AWG - - - ZONE/DEVICE A
 B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C:	16.3 Ohms / 1000 ft
Mutual Capacitance :	65.0 pF/ft
Cond to Shield Cap. :	118.9 pF/ft
Impedance :	40 Ohms
Velocity of Prop :	58 %
Inductance. :	1.3 mH/km

Additional Information :

Cabled OD Avg: 0.077
 Ins Thickness: 0.006
 Jkt Thickness: 0.015
 Flame Rating: Riser
 Certified: UL CL3R/ UL C(UL) CMR
 Max Voltage: 300V
 Packaging: Reelex Box 11.5 x 11.5 x 7.75"
 Packaged Weight: 11 lbs / 5 kgs

(All of the above values are approximated to within +/- 10%)

QMS Registered ISO 9001

2912251.10R.1000