



Structured Cable Products™

Quality Installations Deserve Quality Products

www.scp5e.com
 sales@scp5e.com
 Direct: 954-327-5770
 Toll Free: 866-470-5742

SCP PART#: 22/4-WT-500

UPC: 810070012113

DESCRIPTION:

4C/22 AWG STRANDED BC, SECURITY CABLE, UL CMR PVC JKT- WHITE- 500FT BOX

General Specification of Product :

Final Diameter :	0.131 inches	3.327 mm
Total Cable Weight:	23 kg/km	15 lbs/1000 ft
Conductor :	22 AWG 7x.0097 Bare Copper	
Insulation :	PVC	
Outer Jacket :	PVC	

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/4 - - - (UL) CL3R E198137-SCP
 (UL) C(UL) CMR UNSH 4/C 22 AWG - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5 6
 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C:	15.8 Ohms / 1000 ft	
Mutual Capacitance :	38 pF/ft	
Impedance :	80 Ohms	
Velocity of Prop :	63 %	
Inductance. :	1.4 mH/km	

Additional Information :

Avg Cabled OD: 0.097
 Ins Thickness: 0.006
 Jkt Thickness: 0.015
 Certified: UL CL3R / UL C(UL) CMR
 Flame Rating: Riser
 Max Voltage: 300V
 Packaging: Reelex Box 11.5 x 11.5 x 7.75"
 Packaged Weight: 7 lbs / 3 kgs

(All of the above values are approximated to within +/- 10%)

QMS Registered ISO 9001

3072204.02R.500