

SCP PART#: 22/4PFPLR

Description : 4C/22 AWG SOLID FPLR PVC - 1000 FT BOX

Rev02/22

Conductor : 22 AWG Solid HBC Cond.	
Total Cable Weight : 18 kg/km	Final Diameter : 0.120 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 18.4 Ohms / 1000 ft	Mutual Capacitance : 21 pF/ft
Impedance : 86 Ohms	
Velocity of Prop : 65 %	Inductance. : 1.6 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/4FPLR - - - (UL) FPLR OR
 CL2R E198137 (UL) C(UL) CMR UNSH 4/C 22 AWG - - - ZONE/DEVICE A B C
 D E 0 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.198	NEC Articles: 760 FPLR
Ins Thickness: 0.006	Min. Bend Radius/Minor Axis: .84 inches
Jkt Thickness: 0.015	Operating Temperature : -20°C to 60°C
Certified: UL CL2R/CMR OR FPLR	Standard UL Temp : 60°C
Flame Rating: Riser	
Max Voltage: 300V	

Package Weight: 13 lbs / 5.89 kgs

(All of the above values are approximated to within +/- 10%)