



SPECIFICATION SHEET

15-May-2014

Product Number : 22/4SOL-BL

RoHS

Description : 4C/22 AWG SOLID COPPER, PVC- BLUE- 1000 FT BOX

| | |
|---|---------------------------------|
| Conductor : 22 AWG Solid HBC Cond. | |
| Total Cable Weight : 18 kg/km | Final Diameter : 0.120 inches |
| Insulation : PVC | Jacket : PVC |
| DC Resistance 25°C: 19.5 Ohms / 1000 ft | Mutual Capacitance : 21.9 pF/ft |
| Impedance : 80.8 Ohms | |
| Velocity of Prop : 68 % | Inductance. : 1.3 mH/km |

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/4SOL - - - (UL) CL3R E198137
(UL) C(UL) CMR UNSH 4/C 22 AWG - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5
6 7 8 9 RoHS

| | |
|------------------------|---|
| Cabled OD Avg: 0.082 | NEC Articles: 800, 725 |
| Ins Thickness: 0.006 | Min. Bend Radius/Minor Axis: .84 inches |
| Jkt Thickness: 0.015 | Operating Temperature : -20°C to 60°C |
| Certified: UL CL3R/CMR | Standard UL Temp : 60°C |
| Flame Rating: Riser | |
| Max Voltage: 300V | |

Package Weight: 13 lbs / 5.91 kgs

(All of the above values are approximated to within +/- 10%)