

SCP PART#: 22/8-GY

01/21

Description : 8C/22 AWG STRANDED PVC- GRAY- 1000 FT BOX

| | |
|---|--|
| Conductor : 22 AWG 7x.0097 Bare Copper | |
| Total Cable Weight : 40 kg/km | Final Diameter : 0.167 inches / 4.24mm |
| Insulation : PVC | Jacket : PVC |
| DC Resistance 25°C: 15.3 Ohms / 1000 ft | Mutual Capacitance : 22.7 pF/ft |
| Impedance : 76.5 Ohms | |
| Velocity of Prop : 69 % | Inductance. : 1.3 mH/km |
| Print Notes : | Sequentially marked per 2FT (0 - infinity) |
| Standard Print : | STRUCTURED CABLE PRODUCTS - - - P/N 22/8 - - - (UL) CL3R E198137 (UL) C(UL) CMR UNSH 8/C 22 AWG - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS |
| Cabled OD Avg: 0.138 | NEC Articles: 800, 725 |
| Ins Thickness: 0.006 | Min. Bend Radius/Minor Axis: 1.169 inches |
| Jkt Thickness: 0.015 | Operating Temperature : -20°C to 60°C |
| Certified: UL CL3R/CMR | Standard UL Temp : 60°C |
| Flame Rating: Riser | |
| Max Voltage: 300V | |

Package Weight: 26 lbs / 11.82 kgs

(All of the above values are approximated to within +/- 10%)