



Structured Cable Products®

Quality Installations Deserve Quality Products

www.spcat5e.com
 sales@scpat5e.com
 Direct: 954-327-5770
 Toll Free: 866-470-5742

SCP PART#: F-BCM3-12P-1000 UPC: 817777010404

DESCRIPTION:

Fiber bulk cable -- 12 strand multimode OM3 -- plenum & indoor/outdoor rated -- micro distribution style

Features at a Glance

- Multimode OM3 fiber
- Twelve strand distribution format
- Black color
- Plenum-rated for indoor and outdoor applications
- Water-resistant construction for installation in conduit
- Tight buffered construction
- 3.5 – 5lbs stripping force
- Corning ClearCurve fiber



Duplex Plenum Multimode OM3 Fiber Cable is constructed with twelve internal tight buffers, internal aramid yarn, and one outer riser-rated PVC jacket in distribution format. The fiber cable features a water-resistant jacket and is designed for indoor and outdoor applications.

| Specifications | |
|----------------------------------|-----------------------------------|
| Fiber Count | 12 strands |
| Outer Jacket | Flame retardant PVC, Black color |
| Strength Member | Aramid Yarn |
| Internal Jacket | Tight buffer, flame retardant PVC |
| Outer Jacket Size | 5.8mm |
| Physical Characteristics | |
| Fiber Type | Multimode OM3 |
| Fiber Core Size | 50µm |
| Fiber Make | Corning 50/125 ClearCurve |
| Wavelength | 850 / 1300nm |
| Maximum Attenuation | 3.5dB @ 1.5km |
| Bandwidth (High Performance EMB) | 2000MHz @ 850nm |
| Network Link Length (10Gb/s) | 300m |
| Minimum Bend Radius | 8.7mm |
| Environmental | |
| Storage Temperature | -40°C to +70°C |
| Operating Temperature | -0°C to +70°C |
| Ratings | NFPA262 (flame rating), UL, RoHS |