

SCP PART #: ELAN-1

DESCRIPTION: ELAN CABLE- RG59/U 20 AWG BC + 2C/18 AWG POWER + CAT5E 24 AWG UTP- BUNDLED- PVC JKT- PURPLE- 500 FT SPOOL

CROSS SECTION		PROPERTIES																																																																																																																																											
		Min.Bending Radius: Loaded 20 Times Cable OD Unloaded 10 Times Cable OD Max.Pulling Tension 126 LBS Rated Temperature(°C) -20 ~ +75																																																																																																																																											
CONSTRUCTION		ELETRICAL CHARACTERISTICS																																																																																																																																											
	<table border="1"> <thead> <tr> <th></th> <th>A (2/18AWG)</th> <th>B (RG59/U)</th> </tr> </thead> <tbody> <tr> <td>Conductor</td> <td>BC</td> <td>BC</td> </tr> <tr> <td>Conductor Dia.(+/-0.02mm)</td> <td>0.404*7</td> <td>0.813</td> </tr> <tr> <td>Insulation</td> <td>PVC</td> <td>FPE</td> </tr> <tr> <td>Insulation Dia.(+/-0.1mm)</td> <td>2.1*2</td> <td>3.71</td> </tr> <tr> <td>Color</td> <td>RED/BLACK</td> <td>N</td> </tr> <tr> <td>First Shielding (mm)</td> <td></td> <td></td> </tr> <tr> <td>First Braiding</td> <td></td> <td>BC Wire Braid</td> </tr> <tr> <td>Conductor Dia.(+/-0.01mm)</td> <td></td> <td>0.120</td> </tr> <tr> <td>Conductor Qty.</td> <td></td> <td>128</td> </tr> <tr> <td>Coverage</td> <td></td> <td>88%</td> </tr> <tr> <td>Picks/dm</td> <td></td> <td>22</td> </tr> <tr> <td>Lay length (mm)</td> <td></td> <td>35</td> </tr> <tr> <td colspan="3">Product Standard Certification : UL E310605</td> </tr> <tr> <td colspan="3">1x CAT 5E UTP SOLID 350MHz LAN Cable 24AWG 4Pairs</td> </tr> <tr> <td colspan="3">Complies to TIA/EIA-568-B.2</td> </tr> <tr> <td colspan="3">24AWG Solid Bare Copper Conductor/PE Insulation</td> </tr> <tr> <td colspan="3">(Please see Page 2 of 2 for details)</td> </tr> <tr> <td>Outer Jacket</td> <td></td> <td></td> </tr> <tr> <td>Total Dia (+/-0.2mm)</td> <td></td> <td>13.00±0.20</td> </tr> <tr> <td>Color</td> <td></td> <td>purple</td> </tr> <tr> <td>Length</td> <td></td> <td>500 Ft / Spool</td> </tr> </tbody> </table>		A (2/18AWG)	B (RG59/U)	Conductor	BC	BC	Conductor Dia.(+/-0.02mm)	0.404*7	0.813	Insulation	PVC	FPE	Insulation Dia.(+/-0.1mm)	2.1*2	3.71	Color	RED/BLACK	N	First Shielding (mm)			First Braiding		BC Wire Braid	Conductor Dia.(+/-0.01mm)		0.120	Conductor Qty.		128	Coverage		88%	Picks/dm		22	Lay length (mm)		35	Product Standard Certification : UL E310605			1x CAT 5E UTP SOLID 350MHz LAN Cable 24AWG 4Pairs			Complies to TIA/EIA-568-B.2			24AWG Solid Bare Copper Conductor/PE Insulation			(Please see Page 2 of 2 for details)			Outer Jacket			Total Dia (+/-0.2mm)		13.00±0.20	Color		purple	Length		500 Ft / Spool	<table border="1"> <tbody> <tr> <td>Characteristic Impedance</td> <td>75</td> <td>+/- 3ohm</td> </tr> <tr> <td>Capacitance</td> <td>55</td> <td>pF/m</td> </tr> <tr> <td>Velocity ratio</td> <td></td> <td>81%</td> </tr> <tr> <td>DCR:conductor</td> <td>< 33</td> <td>ohm/km</td> </tr> <tr> <td>DCR:shielding</td> <td>< 13</td> <td>ohm/km</td> </tr> <tr> <td>Sparker</td> <td>4000</td> <td>VCA</td> </tr> <tr> <td>Dielectric Strength</td> <td>2500</td> <td>VCA</td> </tr> <tr> <td>Return loss</td> <td>5-470MHz</td> <td>20 dB</td> </tr> <tr> <td></td> <td>470-1000MHz</td> <td>18 dB</td> </tr> <tr> <td colspan="3">Attenuation at 20 C (dB/100m)</td> </tr> <tr> <td></td> <td>1</td> <td>0.86</td> </tr> <tr> <td></td> <td>3.6</td> <td>1.64</td> </tr> <tr> <td></td> <td>10</td> <td>2.75</td> </tr> <tr> <td></td> <td>71.5</td> <td>7.45</td> </tr> <tr> <td></td> <td>135</td> <td>10.31</td> </tr> <tr> <td></td> <td>270</td> <td>14.76</td> </tr> <tr> <td></td> <td>360</td> <td>17.16</td> </tr> <tr> <td></td> <td>720</td> <td>24.74</td> </tr> <tr> <td></td> <td>1000</td> <td>29.49</td> </tr> <tr> <td></td> <td>1500</td> <td>36.73</td> </tr> <tr> <td></td> <td>2000</td> <td>43.02</td> </tr> <tr> <td></td> <td>2250</td> <td>45.91</td> </tr> <tr> <td></td> <td>3000</td> <td>53.91</td> </tr> <tr> <td colspan="3">RoHS Compliance</td> </tr> </tbody> </table>		Characteristic Impedance	75	+/- 3ohm	Capacitance	55	pF/m	Velocity ratio		81%	DCR:conductor	< 33	ohm/km	DCR:shielding	< 13	ohm/km	Sparker	4000	VCA	Dielectric Strength	2500	VCA	Return loss	5-470MHz	20 dB		470-1000MHz	18 dB	Attenuation at 20 C (dB/100m)				1	0.86		3.6	1.64		10	2.75		71.5	7.45		135	10.31		270	14.76		360	17.16		720	24.74		1000	29.49		1500	36.73		2000	43.02		2250	45.91		3000	53.91	RoHS Compliance		
	A (2/18AWG)	B (RG59/U)																																																																																																																																											
Conductor	BC	BC																																																																																																																																											
Conductor Dia.(+/-0.02mm)	0.404*7	0.813																																																																																																																																											
Insulation	PVC	FPE																																																																																																																																											
Insulation Dia.(+/-0.1mm)	2.1*2	3.71																																																																																																																																											
Color	RED/BLACK	N																																																																																																																																											
First Shielding (mm)																																																																																																																																													
First Braiding		BC Wire Braid																																																																																																																																											
Conductor Dia.(+/-0.01mm)		0.120																																																																																																																																											
Conductor Qty.		128																																																																																																																																											
Coverage		88%																																																																																																																																											
Picks/dm		22																																																																																																																																											
Lay length (mm)		35																																																																																																																																											
Product Standard Certification : UL E310605																																																																																																																																													
1x CAT 5E UTP SOLID 350MHz LAN Cable 24AWG 4Pairs																																																																																																																																													
Complies to TIA/EIA-568-B.2																																																																																																																																													
24AWG Solid Bare Copper Conductor/PE Insulation																																																																																																																																													
(Please see Page 2 of 2 for details)																																																																																																																																													
Outer Jacket																																																																																																																																													
Total Dia (+/-0.2mm)		13.00±0.20																																																																																																																																											
Color		purple																																																																																																																																											
Length		500 Ft / Spool																																																																																																																																											
Characteristic Impedance	75	+/- 3ohm																																																																																																																																											
Capacitance	55	pF/m																																																																																																																																											
Velocity ratio		81%																																																																																																																																											
DCR:conductor	< 33	ohm/km																																																																																																																																											
DCR:shielding	< 13	ohm/km																																																																																																																																											
Sparker	4000	VCA																																																																																																																																											
Dielectric Strength	2500	VCA																																																																																																																																											
Return loss	5-470MHz	20 dB																																																																																																																																											
	470-1000MHz	18 dB																																																																																																																																											
Attenuation at 20 C (dB/100m)																																																																																																																																													
	1	0.86																																																																																																																																											
	3.6	1.64																																																																																																																																											
	10	2.75																																																																																																																																											
	71.5	7.45																																																																																																																																											
	135	10.31																																																																																																																																											
	270	14.76																																																																																																																																											
	360	17.16																																																																																																																																											
	720	24.74																																																																																																																																											
	1000	29.49																																																																																																																																											
	1500	36.73																																																																																																																																											
	2000	43.02																																																																																																																																											
	2250	45.91																																																																																																																																											
	3000	53.91																																																																																																																																											
RoHS Compliance																																																																																																																																													