

SCP PART#: LUT-GREEN-LSZH-BX


Description:

LOW SMOKE ZERO HALOGEN - CONTROL/KEYPAD - 2C/22 AWG
 SHIELDED + 2C/18 AWG STRANDED + DRAIN, EN50575 Dca-s2,d1,a3
 LSZH JKT (Compare to Lutron QS-CBL-LSZH) - WHITE W/GREEN STRIPE-
 305M/1000FT BOX

*Lutron®, Homeworks®, Sivoia®,
 Grafik Eye®, and Quantum Systems®
 are registered trademarks of
 Lutron Electronics Co., Inc
 Structured Cable Products Inc. is
 not affiliated with Lutron and our
 products are not endorsed or
 certified by Lutron.

Standard:

EU RoHS 2011/65 EU Compliant
 IEC 60332-1-2
 EN50575
 REACTION TO FIRE CPR Euroclass Dca-s2,d1,a3



Construction Characteristics:

Conductor A	Material	Stranded Bare Copper
	Size	18AWG X 2C
	Construction	16/0.254+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.24mm
	AVG.Thickness	0.26mm
	Diameter	1.70+/-0.05mm
Colors	Black & Red	
Conductor 1P	Material	Stranded Bare Copper
	Size	22AWG X 2C
	Construction	7/0.254+/-0.004mm
Insulation	Material	FPE
	Min.Thickness	0.56mm
	AVG.Thickness	0.60mm
	Diameter	2.00+/-0.05mm
	Colors	Purple & White
Shield	Drain wire(TC)	7/0.20+/-0.004mm
	Shield	AL Foil
Assembly(2C+1P)	Core wrap	PE Tape
Jacket	Material	LSZH JACKET
	Min.Thickness	0.67mm
	AVG.Thickness	0.75mm
	Diameter	6.35+/-0.20mm
	Rip Cord	Nylon
	Color	Blue with Green Stripe
Bend Radius		Min 15D/100mm

Electrical & Physical Characteristics:

Operating Temperature Range		- 20°C + 70°C	
Conductor Resistance(16AWG)		Max 15.5 ohm/km at 20°C	
Conductor Resistance(22AWG)		Max 53.5ohm/km at 20°C	
18AWG Core/Core Capacitance		130+/-30pf/m	
22AWG Core/Core Capacitance		40+/-15pf/m	
22AWG Core/Screen Capacitance		100+/-30pf/m	
Rated Voltage		Max 300 Volts	
Dielectric Strength		Min AC1.5KV	
Insulation PVC	Unaged	Tensile Strenght	13.8Mpa
		Elongation	100%
	Aged	Tensile Strenght	11.7Mpa(100°C 168h)
		Elongation	50%(100°C 168h)
Jacket	Unaged	Tensile Strenght	11.3 Mpa
		Elongation	100%
	Aged	Tensile Strenght	8.5Mpa(100°C 168h)
		Elongation	50%(100°C 168h)

Marking

STRUCTURED CABLE PRODUCTS --- LUT-GREEN-LSZH --- 2C/22AWG STR SHIELDED + 2C/18AWG STR LSZH
 JKT EN50575:2014 CE Dca-s2,d1,a3 RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***M

Packaging:

Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
17.8kgs/39.02lbs	405*258*418	1000ft/305m Box	30/20