



Description

The 3 x 8 Video Distribution Module is designed for whole house video distribution



Features

- Distributes to eight locations
- Accommodates CATV plus two AUX inputs for combining modulated signals
- Bi-directional traffic with a 5-42 MHz return path

Characteristics

1 X CATV input		80 dBuV Max.
2 x Modulator input		85 dBuV Max.
8 x Broadband (TV Feed) Outputs		F-Type
Gain	CATV to TV OUT	+3 dB
	Modulator to TV OUT	-10 dB
Reverse	TV OUT to CATV	-15 dB
RF Frequency Range CATV		Forward: 50 ; 860MHz Reverse: 5-42MHz
RF Frequency Range Modulator		50 ; 860MHz
RF Return Loss (all ports)		> -10 dB
Isolation	TV OUT - TV OUT	25 dB
	MOD - MOD	25 dB
	MOD - CATV	35 dB
Input Power		External +12V DC regulated Plug Pack @ 500-mA
Connections	RF (all ports)	F-type Female (nickle)
	DC Power In	2.5mm DC Jack, Center Positive
Power Input		DC 12V, 200mA
Power LED		Red Power LED, ON Steady with power applied

Packaging

- Neutral plain white box
- Accessories included:
 - Instruction sheet
 - 12V DC patch lead
 - 12V DC power adapter

Corporate Office:
East Coast Warehouse
5607 Hiatus Road, Suite 500
Tamarac, FL 33321
Phone (954) 327-5770
Fax (954) 327-8176

West Coast Office:
East Coast Warehouse
2514 E Mohawk Lane
Suite 109-110
Phoenix, AZ 85050
Phone (602) 404-2966
Fax (602) 404-2967

Midwest Warehouse:
1184 W. Corporate Dr. Ste D
Arlington, TX 75986
Phone (817) 635-2052
Fax (817) 635-2056

EU Distribution Center:
Trade Boulevard 4
Haven 528
4761 RL Moerdijk
The Netherlands