



Structured Cable Products

Quality Installations Deserve Quality Products

www.scpca5e.com

www.scpca5e.com

SCP PART#: 18/4FPLR -BOX

DESCRIPTION : 4C/18AWG SOLID FPLR PVC -RED-1000FT BOX

Standard: EN50575: 2014 REACTION TO FIRE CLASS Eca

EU RoHS 2011/65/EU Compliant

UL CL2R/CL3R OR FPLR/CMR

Construction Characteristics:

Conductor	Material	SOLID Bare Copper
	Size	18AWG X 4C
	Construction	1.02+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.25mm
	AVG.Thickness	0.28mm
	Diameter	1.5+/-0.05mm
	Colors	Black & Red & White & Green
Jacket	Material	PVC
	Min.Thickness	0.30mm
	AVG.Thickness	0.38mm
	Diameter	4.5+/-0.20mm
	Rip Cord	Nylon
	Color	RED
Bend radius	Min 15D/66mm	

Electrical & Physical Characteristics:

Operating Temperature Range	- 20°C + 75°C		
Minimum installation temperature	0°C + 40°C		
Conductor Resistance(18AWG)	Max 6.8 ohm/1000ft at 25°C		
Dielectric Strength	Min AC1.5KV		
Insulation Resistance	Min 50M Ω *km at 20°C		
Rated Voltage	Max 300Volts		
Marking:			
STRUCTURED CABLE PRODUCTS --- 18/4FPLR --- UNSH 2C 18 AWG SOLID --- E198137 SCP3 (UL)C(UL) CMR ---PVC JKT EN50575:2014 CE Eca EU RoHS EC ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 XXXFEET			
Packaging:			
Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
14.5 kgs	405*258*418	1000ft/BOX	20/30