


SCP PART#: 22/4EPSH -SPL

DESCRIPTION: BALANCED LINE LEVEL AUDIO- 4C/22 AWG TC TWISTED PAIR, EACH PAIR AL FOIL Dca, SHIELD W/DRAIN, UL CL2R, EN50575:2014 PVC JKT- GRAY- 1000FT/305M SPOOL



Standard: EN50575: 2014 REACTION TO FIRE CLASS Dca
EU RoHS 2011/65/EU Compliant

Construction Characteristics:

Conductor	Material	Stranded Tinned Copper
	Size	22AWG X 4C
	Construction	7/0.25+/-0.004mm
Insulation	Material	HDPE
	Min.Thickness	0.228mm
	AVG.Thickness	0.25mm
	Diameter	1.27+/-0.05mm
	Colors	Black & Red + Black & White or Green & White
Shield	Drain wire(TC)	7/0.25+/-0.004mm
	Shield	AL Foil
	PET Tape	YES
Jacket	Material	PVC
	Min.Thickness	0.72mm
	AVG.Thickness	0.80mm
	Diameter	6.30+/-0.20mm
	Rip Cord	Nylon
	Color	Gray
Bend radius	Min 15D/95mm	

Electrical & Physical Characteristics:

Operating Temperature Range	- 20°C + 75°C
Minimum installation temperature	0°C + 40°C
Conductor Resistance(22AWG)	Max 53.5ohm/km at 20°C
Dielectric Strength	Min AC1.5KV
Rated Voltage	Max 80Volts

Marking:

STRUCTURED CABLE PRODUCTS --- 22/4EPSH --- 4C/22AWG TC AL FOIL+DRAIN -- PVC JKT
EN50575:2014 CE Dca EU RoHS EC ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***FT

Packaging:

Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
18.5kgs/40.785lbs	360*220*160	1000ft/SPOOL	36