

<b>SCP PART#: 22/6FPLR</b>
----------------------------

DESCRIPTION: 6C/22AWG SOLID FPLR PVC-RED-1000FT BOX

**Standard:** EN50575: 2014 REACTION TO FIRE CLASS Dca  
 EU RoHS 2011/65/EU Compliant

**Construction Characteristics:**

Conductor	Material	Solid Bare Copper
	Size	22AWG X 6C
	Construction	0.643+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.20mm
	AVG.Thickness	0.25mm
	Diameter	0.95+/-0.05mm
	Colors	Black & Red & White & Green & Brown & Blue
Jacket	Material	PVC
	Min.Thickness	0.3mm
	AVG.Thickness	0.40mm
	Diameter	3.6+/-0.20mm
	Rip Cord	Nylon
	Color	RED
Bend radius	Min 15D/65mm	

**Electrical & Physical Characteristics:**

Operating Temperature Range	- 20°C + 75°C		
Conductor Resistance(22AWG)	Max 60 ohm/km at 20°C		
Dielectric Strength	Min AC1.5KV		
Rated Voltage	Max 80Volts		
Marking:			
STRUCTURED CABLE PRODUCTS --- 22/6FPLR --- UNSH 6C/22AWG BC SOLID ----- E198137 SCP3 (UL) C(UL) CL3R CMR----- PVC JKT RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***M DDMMYY			
Packaging:			
Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
10.5kgs	350X260X350	1000ft/Box	36