

SCP PART#: ACC-1-P

Rev06/22

Description:

PLENUM ACCESS CONTROL COMPOSITE- 2C/22 AWG + 4C/22 AWG + 4C/18 AWG +
6C/22 AWG SHIELDED- BUNDLED- UL CMP JKT- 500 FT SPOOL- YELLOW

General Specification of Product :

Final Diameter :	0.415 inches	10.541 mm
Total Cable Weight:	175.0 kg/km	117.6 lbs/1000 ft
Conductor :	ACC-1-PL - 18 AWG 7 AWG SBC - 22 AWG 7 AWG SBC,	
Insulation :	0.008" PVC FT6	
Inner Jacket :	0.018" PVC FT6	
Outer Jacket :	0.020" PVC FT6	

Standard Print : PLENUM ACCESS CONTROL - - - (UL C(UL) CMP E198134-SCP 12C 22 4C
18 - - - - - 2C/22 AWG STR BC + 4C/22 AWG STR BC + 4C/22AWG STR BC
+ 4C/18 AWG STR BC + SH 6C/22 AWG STR BC ROHS- - - ZONE A B C D E O
1 2 3 4 5 6 7 8 9

Additional Information :

UNSH 4/C 18/7 SBC - White with Purple Stripe
DC Resistance: 25°C 6.8 Ohms/1000'
Mutual Capacitance: 23.7 pF/ft
Impedance: 70 Ohms
Velocity of Prop: 63%
Inductance: 1.3 (mH/km)

SHLD 3/PR 22/7 SBC - White with Yellow Stripe
DC Resistance: 25°C 16.1 Ohms/1000'
Mutual Capacitance: 35.4 pF/ft
Avg. Shld Capacitance: 60.1 pF/ft
Impedance: 60 (Ohms)
Velocity of Prop: 61%
Inductance: 1.3 mH/km)

UNSH 2/C 22/7 SBC - White with Green Stripe
DC Resistance: 25°C 16.3 Ohms/1000'
Mutual Capacitance: 20 pF/ft
Impedance: 80 (Ohms)
Velocity of Prop: 63%
Inductance: 1.4 mH/km)

UNSH 4/C 22/7 SBC - White with Red Stripe
DC Resistance: 25°C 16.3 Ohms/1000'
Mutual Capacitance: 20 pF/ft
Impedance: 80 Ohms
Velocity of Prop: 62%
Inductance: 1.5 (mH/km)

Certified: C(UL) CMP
Flame Rating: Plenum