www.scpcat5e.com sales@scpcat5e.com Direct: 954-327-5770

Toll Free: 866-470-5742

UPC: 817777011760

## **SCP PART#: F-BCM3-2R-1000**

## **DESCRIPTION:**

Fiber bulk cable -- 2 strand multimode OM3 -- riser & indoor rated -- micro distribution style Aqua 1,000ft Spool

## Features at a Glance

- Multimode OM3 fiber
- Two strand distribution format
- · Aqua color
- Riser-rated for indoor applications
- Tight buffered construction
- 3.5 5lbs stripping force
- Corning ClearCurve fiber



Duplex Riser Multimode OM3 Fiber Cable is constructed with two internal tight buffers, internal aramid yarn, and one outer riser-rated PVC jacket in distribution format. The fiber cable is designed for indoor applications and features Corning ClearCurve fiber.

Specifications	
Fiber Count	2 strands
Outer Jacket	Flame retardant PVC, Aqua color
Strength Member	Aramid Yarn
Internal Jacket	Tight buffer, flame retardant PVC
Outer Jacket Size	4.4mm
Physical Characteristics	
Fiber Type	Multimode OM3
Fiber Core Size	50μm
Fiber Make	Corning 50/125 ClearCurve
Wavelength	850 / 1300nm
Maximum Attenuation	3.5dB @ 1.5km
Bandwidth (High Performance EMB)	2000MHz @ 850nm
Network Link Length (10Gb/s)	300m
Minimum Bend Radius	6.6mm
Environmental	
Storage Temperature	-40°C to +70°C
Operating Temperature	-20°C to +70°C
Ratings	UL1666 & UL1685 FT4 (flame rating), RoHS

Date: 12/23/2019