

**SCP PART#: 14/2SH-GY**

**DESCRIPTION:**

Rev03/23

2C/14 AWG 19-Strand BC, Shielded, Multipurpose, UL CMR PVC Jkt- Gray - 1000 FT Spool

General Specification of Product :

Final Diameter :	0.227 inches	5.766 mm
Total Cable Weight:	62.0 kg/km	41.7 lbs/1000 ft
Conductor :	14 AWG 19 Stranded Bare Copper	
Insulation :	PVC	
Shield :	Foil Shield	
Drain \ Ground:	24 AWG 7 Stranded Tinned Copper	
Outer Jacket :	PVC	

Print Notes :            Sequentially marked per 2FT (0 - infinity)  
 Standard Print :        STRUCTURED CABLE PRODUCTS - - - P/N 14/2SH - - - (UL) CL3R  
                                   E198137-SCP (UL) C(UL) CMR SHIELDED 2/C 14 AWG AUDIO ONLY - - -  
                                   ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C:	2.6 Ohms / 1000 ft
Mutual Capacitance :	65 pF/ft
Cond to Shield Cap. :	119 pF/ft
Impedance :	35 Ohms
Velocity of Prop :	63 %
Inductance. :	1.2 mH/km

Additional Information :

Cabled OD Avg: 0.193  
 Ins Thickness: 0.011  
 Jkt Thickness: 0.017  
 Certified: UL CL3R / UL C(UL) CMR  
 Flame Rating: Riser  
 Max Voltage: 300V  
 Packaging: Plywood Spool 12 x 7 x 5"  
 Packaged Weight: 42 lbs / 20 kgs

( All of the above values are approximated to within +/- )0%