



MATERIAL

PLASTIC HOUSING : ABS high-impact UL94V-0 thermoplastic
INSERT:Brass 3604 Surface gold plating

PHYSICAL CHARACTERISTICS

OPERATING TEMPERATURE RANGE : -10 C TO 60 C
STORAGE TEMPERATURE RANGE : -40 C TO 68 C
HUMIDITY : 10%~90%RH

ELECTRICAL

IMPEDANCE: 75 ohm
FREQUENCY RANGE: 0~3 GHz
WORKING VOLTAGE: 250 VRMS max.
DIELECTRIC WITHSTANDING VOLTAGE: 500VRMS min.
VSWR: 1.35 max
CONTACT RESISTANCE: 1.Center Contact: 5 Milliohms Max.
2.Outer Contact: 1 Milliohms Max.
INSULATOR RESISTANCE: 1000 Megohms min.

Colors Available: Almond & White

Scale	1.5:1	All Copy Rights Reserved	
3rd Angle Projection		RCA SNAP IN MODULE, GOLD-PLATED-White Bezel	
Unit	mm	SCP P/N 243WT-XX	
Date	2015-09-16		
Tolerance		Drawn by FHL	Checked by Santiago
~20 ±0.2	~50 ±0.4		
ANGLE		±2°	