


SCP PART#: SP-4.0/2-LSZH-BK-305M

Description:

Commercial Speaker Cable - B2ca Rated - 2 Cond/4.0mm² Oxygen Free Copper, EN50575 B2ca-s1a,d1,a2 Low Smoke Zero Halogen, Indoor/Outdoor UV Sun Res Jkt- Black- 305m/1000ft Wooden Spool



Construction Characteristics:

Conductor	Material	Stranded Bare Copper
	Size	4.0mm ² *2C 56 stranded
	Construction	0.30+/-0.005mm
Insulation	Material	LSZH
	AVG.Thickness	0.45mm
	Diameter	3.5+/-0.15mm
	Colors	Red,Black
Jacket	Material	LSZH
	Nom.Thickness	0.75mm
	Diameter	8.5 + /-0.40mm
	Rip Cord	Yes
	Color	Black(similar to RAL9004)

Electrical & Physical Characteristics

Operating Temperature Range		-20°C ~ +80°C
Voltage Rating		300 V
Conductor DC resistance (20 °C)		<=4.95 Ohms
Sheath Physical Properties		100 °C*168h
Before Aging	Tensile Strength	>=10.0Mpa
	Elongation	>=125%
After Aging	Tensile Strength	>=8.0Mpa
	Elongation	>=100%

Markings (squares are just for identifying space numbers ,will not be printed)

STRUCTURED CABLE PRODUCTS -- SP-4.0/2-LSZH -- Commercial Speaker Cable / Audio Cable -- 2C/4.00mm² 56x0.30mm Strand Oxygen Free Copper Indoor/Outdoor UV Sun Res LSZH JKT EN50575 B2ca-s1a,d1,a2 EU RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***M MM/YY LOT # 0502248

Packaging

Approx Weight	Approx Dimension (Spool)	Package	Spools per pallet	Pallet weight
39.8kg/spool	38x20x32cm	305M/spool	24 spools	955kg